



LCR-6000 Series

Precision LCR Meter

FEATURES

- 3.5" Color LCD
- 5 Models (10 Hz to 2 kHz/20 kHz/100 kHz/200 kHz/300 kHz)
- Consecutive Test Frequency
- Basic Accuracy : 0.05 %
- Measuring Speed up to 25 ms (Max.)
- Full Frequency Range or Spot OPEN/SHORT
- 16 Major/Secondary Parameter Measurement Combinations and Two Additional Monitoring Parameters (Maximum Four Different Parameters Can be Shown Simultaneously)
- DCR Measurement and Internal D.C. Bias Voltage (± 2.5 V)
- PASS/FAIL Judgment
- Auto Level Control (ALC) Function
- BIN Function Provides 9 BIN and 1AUX, Totally 10 BIN
- 10 Steps Listed Tests to Select Different Frequency, Voltage and Current Criteria
- Standard Interface : RS-232C, Handler and USB Host/Device
- Compact Size, Ideal for Automatic Equipment (2 U, 1/2 Rack)

GW INSTEK
Simply Reliable

GW Instek introduces the brand new high precision LCR meter - LCR-6000 series, which, with five models, has a test frequency range extending from 2 kHz/20 kHz/100 kHz/200 kHz/300 kHz (maximum) and with 0.05 % basic accuracy. The compact size design, 2 U height and 1/2 rack, is one of the practical features of the series which is the optimum space saver suitable for either bench top or system rack. The compacted LCR-6000 series with abundant features is absolutely the excellent tool for R&D, production test, IQC, etc. on implementing each test stages for passive components.

The LCR-6000 series provides rich functionalities with the compact size. First of all, the entire series adopts 3.5-inch color LCD and features opulent display parameters. In addition to simultaneously displaying setting criteria and measurement results, the series increases two additional monitoring parameters. In other words, there are four parameters, primary/secondary and two monitoring, simultaneously shown on the screen that tremendously enhances the measurement efficiency. The enlarge display mode not only emphasizes the measurement results, but also provides PASS/FAIL judgment to facilitate a rapid and convenient test result.

Convenience is one of the unique features. The LCR-6000 series comes equipped with two zero methods, which are full frequency range and spot. Users, without turning off the power and changing test fixture, can freely change frequency within the provided frequency range to conduct measurements. By so doing, tremendous time can be saved from repeatedly executing zero operation. Additionally, frequency range of the series is consecutive that allows users to input precise frequency value to conduct the most genuine test on components.

The LCR-6000 series also features diverse ancillary measurements to meet the measurement requirements of different materials. For instance, the series provides the automatic level control (ALC) function to satisfy the test voltage requirement of MLCC. For inductive component measurements, the series provides the adjustable test current function and the D.C. resistance measurement function. The optional external bias current adapter (± 2.5 A) is to satisfy the measurement requirements. With respect to the D.C. bias voltage test for capacitive components requirements, the series allows users to conduct verification measurement on materials by its internal ± 2.5 V adjustable voltage or via an optional external bias voltage adapter (± 45 V). Furthermore, 10 steps of listed test functionalities allow users to set testing parameters (either by frequency, or voltage, or current) for each step based on users' requirements in order to observe the trend of DUT characteristics.

The LCR-6000 series has 10 memory sets defined by panel setting criteria to facilitate users in selecting test criteria and saving time in repeated settings. 10,000 measurement result storage capability can easily record measurement results instantaneously. The USB host allows easy access to recorded results without connecting the series to the PC. The USB host also allows USB to retrieve and save screen so as to assist users in compiling setting guidelines.

For the external control, the LCR-6000 series provides handler interface and collocates with its measurement sorting function (9BIN, AUX: 1BIN) to facilitate the connection with sorting machine so as to sort out the materials. For remote control and measurement result retrieval requirements, the LCR-6000 series provides RS-232C to assist setting control or measurement result retrieval via the PC commands. Additionally, the free PC software gives users an instant tool to store measurement results that saves time in developing programs.

The brand new compacted LCR-6000 series can effectively improve the limitation of space. Diverse measurement functionalities and display methods are making the series the high CP ratio choice in meeting the requirements of R&D, component assessment for engineering departments, category sorting requirements for component production, and IQC for verification on component specifications.


PANEL INTRODUCTION



CE	USB host	PC Software	RS-232	Handler	LabVIEW Driver
USB					

1. 3.5" Large TFT LCD Provides Setting Parameters and Measurement Result Observation Simultaneously
2. Corresponding Functional Keys Provide More Intuitive And Fast Operation
3. Maximum 4 Measuring Parameters Can Be Shown
4. Usb Host For Data Storage and Display Screen Retrieval
5. Four Wire Measurement Terminal
6. RS-232C/USB Device Port (Standard)
7. Handler Port (Standard)
8. Universal Power Input


A. Consecutive Frequency and Convenient Zero Function



Consecutive and Adjustable Frequency **Selectable Fixture Zeroing Methods**
Freely Input Frequency Within Provided **Full Frequency Range Zero or Spot Zero**
Frequency Range

The LCR-6000 series, within the provided frequency range, features consecutive and adjustable frequency capability which allows users to conduct measurement and analysis on components with the most genuine frequency requirements. For OPEN/SHORT fixture compensation function, the LCR-6000 series is equipped with full frequency range zero and spot zero selections. After executing full frequency range zero, users, under the conditions of not turning off the power and not changing test fixture, can freely change test frequency for the LCR-6000 series to execute component measurements that tremendously saves time in repeatedly zeroing test fixture after changing frequency.

B. Rich and Diverse Information Display




MEAS Display
Parameter Setting and Four
Measurement Parameters

ENLARGE Display
Enlarge Measurement Results and
Include PASS/FAIL Judgment

The measurement result display of the LCR-6000 series not only reveals major and secondary measurement parameters but also includes two monitoring parameters. Therefore, four DUT related parameters can be simultaneously shown on the display screen to save time if repeated measurements are required. With respect to display screen, the LCR-6000 series features diverse display to meet users' observation requirements. For instance, MEAS display shows setting parameters and measurement results at the same time; ENLARGE display focuses on measurement results and PASS/FAIL judgment is available, which is conducive to assist engineers to swiftly obtain the validity of measurement results.


C. Diverse Ancillary Measurement Functions



Automatic Level Control
Ideal for Measuring Components
With Voltage Requirements



Internal Bias (±2.5 V Adjustable)
Ideal for Capacitive Components'
Characteristic Tests




D.C. Resistance Measurement
Ideal for inductive components' D.C.
Characteristics Verification


To satisfy the diverse measurement application requirements for different components and materials, the LCR-6000 series collocates with many auxiliary measurement functions. For capacitor measurement, Automatic Level Control (ALC) is mainly for component which requires a constant or rated test voltage such as multi-layer ceramic capacitor (MLCC). An internal D.C. bias voltage (±2.5 V, internal) is allowing simulating A.C. and D.C.

coexistence to learn capacitance variation. For inductor measurement, the D.C. resistance measurement function is to validate D.C. resistance characteristics. Additional, the LCZ function is to quickly identify components' characteristics. When the function is activated, the LCR-6000 series will automatically determine DUTs' characteristics and reveal the optimum parameters to show the measurement results.

D. 10 Points Tests and PC Software




Listed Tests
Variation Criteria Based Upon
Frequency or Voltage/Current



On Software - Characteristic Curve
Provide More Delicate Characteristic
Variation Trend

The LCR-6000 series provides the 10 points listed test function, which allows users to define a set of DUT measurement parameters (such as Cs-Rs) and to set 10 test criteria of category (either by frequency or by voltage or by current) but different values to conduct measurements. Through this function, users can rapidly and clearly obtain DUT's characteristic variation trend to determine the adaptability of DUT's practical applications. The measurement results can be recorded directly in the internal memory and be transferred to the PC through USB. The LCR-6000 series also provides free PC software (maximum 1,000 points listed tests) in order to satisfy users' analytical requirements on delicate variation.

E. Standard Interface



Standard Interface

For interface connectivity, the LCR-6000 series comes equipped with Handler interface and RS-232C/USB Device interface. Handler outputs 10 BIN (9 BIN, AUX: 1 BIN) sorting results that is best for external connection control, for instance, connecting to a sorting machine to conduct components' sorting operation. RS-232C/USB Device is suitable for remote control and measurement results retrieval. The PC gives commands to control settings or to read measurement results so as to achieve the requirements of verifying automotive applications.

SPECIFICATIONS

TEST FREQUENCY		LCR-6300 : 10 Hz to 300 kHz($\pm 0.01\%$) (4 digits resolution) LCR-6200 : 10 Hz to 200 kHz($\pm 0.01\%$) (4 digits resolution) LCR-6100 : 10 Hz to 100 kHz($\pm 0.01\%$) (4 digits resolution) LCR-6020 : 10 Hz to 20 kHz($\pm 0.01\%$) (4 digits resolution) LCR-6002 : 10 Hz to 2 kHz($\pm 0.01\%$) (4 digits resolution)
OUTPUT IMPEDANCE		30 Ω / 50 Ω / 100 Ω selectable
BASIC ACCURACY	Slow / Med Fast	0.05 % 0.1 %
TEST SPEED		FAST : 25 ms / MED : 100 ms / SLOW : 333 ms
TEST SIGNAL LEVELS	AC Voltage Current DCR	10.00 mV to 2.00 V ($\pm 10\%$) CV : 10.00 mV to 2.00 V ($\pm 6\%$) 100.0 μ A to 20.00 mA ($\pm 10\%$) CC : 100.0 μ A to 20.00 mA ($\pm 6\%$) (@2 VMax) +2 V, 0.066 A (Max.), Output impedance fixed 30 Ω
DC BIAS	Internal	± 2.5 V (0.5 % + 0.005 V)
DISPLAY RANGE	R, X, Z G, B, Y L C D Q θ d θ r DCR $\Delta\%$	0.00001 Ω to 99.9999 M Ω 0.01 nS to 999.999 S 0.00001 μ H to 9999.99 H 0.00001 pF to 9999.99 mF 0.00001 to 9.99999 0.00001 to 99999.9 -179.999 $^\circ$ to 179.999 $^\circ$ -3.14159 to 3.14159 0.00001 Ω to 99.9999 M Ω -99999 % to 99999 %
TEST MODE	Combinations Monitor Parameter (2 Selectable)	Cs-Rs, Cs-D, Cp-Rp, Cp-D, Lp-Rp, Lp-Q, Ls-Rs, Ls-Q, Rs-Q, Rp-Q, R-X, DCR, Z- θ r, Z- θ d, Z-D, Z-Q, Auto LCZ Z, D, Q, Vac, Iac, Δ , $\Delta\%$, θ r, θ d, R, X, G, B, Y
LISTED MODE		10 steps
BIN FUNCTION		Comparator (9 BIN, AUX: 1 BIN)
MEMORY	INT – Panel Setting INT – Measured Data USB Storage	10 file name 10000 Data(.csv) 10 file name for setting, 9999 file name for data, 999 Log file for LCD screen
OTHER FUNCTION	Auto Level Control (ALC) Average Trigger Delay Judgment Screen Capture	ON/OFF 1 to 256 times INT / MAN / EXT / BUS 0 ms to 60 s PASS / FAIL Saving in to USB (Bmp form)
DISPLAY		3.5" LCD, RGB color (320 x 240)
INTERFACE		RS-232(SCPI), Handler, USB Host/Device
POWER SOURCE		AC 100 V to 240 V, 50 to 60 Hz, Max. 15 W
DIMENSIONS & WEIGHT		265(W) mm x 107(H) mm x 312(D) mm ; Approx. 3 kg

Specifications subject to change without notice. CR-6000GD1BH 202604

ORDERING INFORMATION

LCR-6300	10 Hz to 300 kHz Precision LCR Meter
LCR-6200	10 Hz to 200 kHz Precision LCR Meter
LCR-6100	10 Hz to 100 kHz Precision LCR Meter
LCR-6020	10 Hz to 20 kHz Precision LCR Meter
LCR-6002	10 Hz to 2 kHz Precision LCR Meter

ACCESSORIES

Safety Sheet x 1, Power Cord x 1, Test Fixture LCR-06B x 1

OPTION

LCR-16	± 45 V DC Bias Voltage Box	LCR-17	± 2.5 A DC Bias Current Box
LCR-DB1	± 200 V DC Bias Voltage Box (Freq. up to 2 MHz)		

OPTIONAL ASSESSORIES

LCR-05	Test Fixture for Axial & Radial Lead Components	GTL-246	USB Cable, USB 2.0 A-B TYPE CABLE, 4 P
LCR-06B	Kelvin Clip Test Lead	GRA-422	Rack Mount Kit, 19" 2 U size
LCR-07	Test Fixture, Two-Wire with Alligator Clips	GRA-454	Rack Mount Kit, 19" 2 U size for one or two sets
LCR-08A	Test Fixture (Tweezers) for SMD/Chip Components		
LCR-15	Test Fixture for SMD/Chip Components (0201 to 1812)		
GTL-232	RS-232C Cable, 9-pin Female to 9-pin, null Modem for Computer, Approx. 2 m		

FREE DOWNLOAD

PC Software LCR-6000 Series Driver LabVIEW Driver

LCR-05



LCR-06B



LCR-07



LCR-08A



LCR-15



LCR-16



LCR-17



Global Headquarters

GOOD WILL INSTRUMENT CO., LTD.

T +886-2-2268-0389 F +886-2-2268-0639

China Subsidiary

GOOD WILL INSTRUMENT (SUZHOU) CO., LTD.

T +86-512-6661-7177 F +86-512-6661-7277

Malaysia Subsidiary

GOOD WILL INSTRUMENT (SEA) SDN. BHD.

T +604-6111122 F +604-6115225

Europe Subsidiary

GOOD WILL INSTRUMENT EURO B.V.

T +31(0)40-2557790 F +31(0)40-2541194

U.S.A. Subsidiary

INSTEK AMERICA CORP.

T +1-909-399-3535 F +1-909-399-0819

Japan Subsidiary

TEXIO TECHNOLOGY CORPORATION.

T +81-45-620-2305 F +81-45-534-7181

Korea Subsidiary

GOOD WILL INSTRUMENT KOREA CO., LTD.

T +82-2-3439-2205 F +82-2-3439-2207

India Subsidiary

GW INSTEK INDIA LLP.

T +91-80-4203-3235

GW INSTEK

Simply Reliable



Website



Facebook



LinkedIn