GPP-1205/1323

Programming Linear DC Power Supply







FEATURES

- * Voltage Resolution: 1 mV / 0.1 mV
- * Current Resolution: Three levels: 0.1 mA / 0.01 mA (H), 10 μΑ / 1 μΑ (M), 1 μΑ / 0.1 μΑ (L)
- * Output Modes: Constant Voltage (CV) / Constant Current (CC)
- * Switchable Power Supply & Electronic Load Function
- * Output Control: On/Off with delay function
- * Slew Rate Control for Voltage & Current
- * Remote Sense for Voltage Compensation
- * Sequence Programming for Power Output
- * Bleeder Circuit Control
- * Voltage Averaging & Data Collection
- * External Series & Parallel Connection Support
- * Safety Protections: OVP, OCP, OTP, Reverse Polarity, Panel Lock
- * Communication Interfaces: USB-TMC/CDC, LAN, Optional GPIB
- * Display: 2.4-inch TFT-LCD with three modes
- * Temperature-Controlled Fan
- * Rack Compatibility: Supports GRA-441-J/E

The GPP-1000 series is a high-precision programmable DC power supply designed for accuracy in precision testing. It features voltage resolution up to 1 mV / 0.1 mV and three levels of current resolution, with a maximum of 1 μ A / 0.1 μ A. Supporting both Constant Voltage (CV) and Constant Current (CC) modes, it also includes a switchable power supply and electronic load function. The series consists of two models: GPP-1205 (20 V / 5 A / 100 W) and GPP-1323 (32 V / 3 A / 96 W), offering flexible output options.

Equipped with Remote Sense functionality, the GPP-1000 series compensates for voltage drops due to lead resistance, ensuring accurate output. It supports data logging and external series/parallel connections of up to four units for higher power applications.

Safety features include OVP, OCP, OTP, and reverse polarity protection, along with a front panel lock to prevent accidental operation. Communication interfaces include USB-TMC/CDC and LAN, with optional GPIB for remote control. A 2.4-inch TFT-LCD provides clear data visualization, while an intelligent temperature-controlled fan enhances cooling efficiency.

With its high resolution, versatile communication options, robust safety protections, and flexible application modes, the GPP-1000 series is a powerful solution for R&D, testing, and production environments. It exemplifies modern test equipment trends, making testing more accurate, convenient, and efficient.

European Type Jack Terminal





APPLICATIONS

- * Research & Education
- * HiFi Audio Circuit
- * Devie/Components Testing
- * 3C Products Testing







Website

acebook

LinkedIn

SPECIFICATIONS		GPP-1323	GPP-1205	
OUTPUT RATING		GFF-1323	GPP-1203	
Output Voltage		0.000 V to 32.000 V	0.000 V to 20.000 V	
Output Voltage Output Current		0.0000 V to 32.000 V 0.0000 A to 3.0000 A	0.0000 V to 20.000 V	
Output Power		96 W	100 W	
CONSTANT VOLTAC	E OPERATION	20 11	100 11	
Line Regulation	0	± (0.01 % of setting + 3 mV)		
Load Regulation		$\leq 0.01 \% + 3 \text{ mV (rating current} \leq 3 \text{ A)}$		
		$\leq 0.02 \% + 5 \text{ mV (rating current} > 3 \text{ A)}$		
Transient Response		< 100 µs		
Ripple Noise		0.8 mVrms		
Setting Range		0 V to 33.600 V	0 V to 21.000 V	
Rise Time		≤ 100 ms		
Fall Time		≤ 100 ms		
	sing Compensation Voltage	0.5 V		
(Single Line)				
Temperature Coefficien		300 ppm/°C		
CONSTANT CURREN	11 OPERATION			
Line Regulation		≤ 0.1 % + 3 mA		
Load Regulation		≤ 0.1 % + 3 mA	0.4 + 5.2500.4	
Setting Range		0 A to 3.1500 A	0 A to 5.2500 A	
Ripple Noise (Arms)	+ (TVD.)	≤ 2 mArms		
Temperature Coefficien	ı (11P.)	300 ppm/°C		
RESOLUTION	Dungung maring at Day attend	1 mV / 0.1 mV		
/oltage Current	Programming/Readback Programming/Readback	1 mV / 0.1 mV		
METER	riogramming/keaddack	(High) 0.1 mA / 0.01 mA; (Middle) 10 μA / 1 μA; (Low) 1 μA/ 0.1 μA		
Full Scale	Voltage/Current	33.6000 V / 3.1500 A	21.0000 V / 5.2500 A	
ruii Scale Programming	Voltage/Current Voltage/Current	5 digits / 5 digits	21.0000 V / 3.2300 A	
Programming Readback Resolution	Voltage/Current	6 digits / 6 digits		
Setting Accuracy	. Jimpe/ Current	Voltage: \pm (0.03 % of reading + 10 mV); Current: \pm (0.3 % of reading + 10 mV)	A) (H)	
Setting Accuracy		Current: \pm (0.3 % of reading + 10 m/s); Current: \pm (0.3 % of reading + 0.1 mA) (H)		
Readback Accuracy		Voltage: ± (0.03 % of reading + 10 mV); Current: ± (0.3 % of reading + 10 mA) (H)		
,		Current: ± (0.3 % of reading + 1 mA) (M); Current: ± (0.3 % of reading + 0.1		
DC LOAD MODE		, , , , , , , , , , , , , , , , , , ,	, (-)	
Display	Voltage	3.000 V to 32.000 V	3.000 V to 20.000 V	
	Current	0 A to 3.0000 A	0 A to 5.0000 A	
	Power	96 W	100 W	
CV Mode	Setting Range	3.000 V to 32.000 V	3.000 V to 20.000 V	
	Setting/Readback	≤ 0.1 % + 30 mV	3.000 1 10 20.000 1	
	Resolution	1 mV		
CC Mode	Setting Range	0 A to 3.0000 A	0 A to 5.0000 A	
			0 A to 3.0000 A	
	Setting/Readback	$\leq \pm 0.3 \% + 10 \text{ mA}$		
PROTECTION *1	Resolution	0.1 mA		
OVP	Setting Range	1.8 V to 35.2 V	1.0 V to 22.0 V	
OVP	Setting Accuracy	± 100 mV	1.0 V to 22.0 V	
	Operation	Turns the output off, displays OVP		
ОСР	Setting Range	0.15 A to 3.3 A	0.25 A to 5.5 A	
	Setting Accuracy	± 20 mA	0.23 // 10 3.3 //	
	Operation	Turns the output off, displays OCP		
ОТР	Operation	Turns the output off, displays OTP		
Insulation Resistance		Between chassis and terminal : 20 MΩ or above (DC 500 V)		
		Between chassis and DC power cord : 30 M Ω or above (DC 500 V)		
SERIES AND PARALL	EL CAPABILITY			
Parallel Number		4 units		
Series Number		4 units		
ADVANCED FUNCTI	ON			
Trigger Signal *2	Trigger Input	A high- or low-level CMOS signal is applied for 100 μs or longer.		
		It receives a pulse to perform actions like power output, V/I set operation or	•	
	Trigger Output	Trigger output: approx. 3.3 V Pulse width: approx. 1ms, Output impedance: approx. 50 Ω		
		It outputs a pulse when power output, V/I set operation or memory recall is	executed.	
Status Signal Output	Output ON/OFF Status	Turns on when the output is on		
*2 *3	CV Status	Turns on during CV operation		
	CC Status	Turns on during CC operation		
	ALM Status	Turns on when the power is turned on		
CENTEDAL CONCUESO	PWR ON Status	Turns on when the power is turned on		
GENERAL SPECIFICA	THOM2	2.4 in the TETLICE		
Display	LAN	2.4-inch TFT LCD		
Interface	LAN	MAC Address, Gateway IP Address, Instrument IP Address, Subnet Mask		
	USB GPIB (Factory Optional)	Type A: Host, Type B: Slave, Speed: 1.1/2.0, USB-CDC/TMC SCPI-1993, IEEE 488.2 compliant interface		
	. , , ,		0 °C +- 40 °C	
Onesetin - Free		Indoor use, Overvoltage Category II, Altitude: ≤ 2000 m, Ambient temperatur	re: U *C to 40 *C,	
Operating Environment		Relative humidity: 20 % to 80 % RH; No condensation		
			La sandanastian	
Storage Environment		Ambient temperature: -20 °C to 70 °C, Relative humidity: 20 % to 85 % RH; N	NO CONGENSATION	
Storage Environment Power Source		AC (100 V, 120 V, 220 V, 240 V) ± 10 %, 50 or 60 Hz	NO CONGENSATION	
Operating Environment Storage Environment Power Source Power Consumption		AC (100 V, 120 V, 220 V, 240 V) ± 10 %, 50 or 60 Hz 300 VA	No condensation	
Storage Environment Power Source		AC (100 V, 120 V, 220 V, 240 V) ± 10 %, 50 or 60 Hz		

Note: *1. When the protection function is activated, it turns the output off, displays OVP, OCP, or OTP.

*2. EXT I/O connector on the rear panel.

*3. Open collector output: Maximum voltage of 30 V and maximum current of 8 mA. The common line for the status pins is floating (isolated voltage of 60 V or less), it is isolated from the output and control circuits.

The specifications apply when the GPP-1205/1323 are powered on for at least 30 minutes under +20 °C to +30 °C.

ORDERING INFORMATION 100 W Single Channel Programming Linear DC Power Supply (USB, LAN) (20 V /5 A) 96 W Single Channel Programming Linear DC Power Supply (USB, LAN) (32 V/3 A) GPP-1205 GPP-1323

ACCESSORIES:

Standard Type Jack Terminal:

Power Cord x 1, Packing List x 1, Test lead GTL-104A

OPTION (Manufacturer Installed Only)

GPIB interface OPTIONAL ACCESSORIES

GTL-104A

Test Lead, U-type to Alligator Test Lead, Max. Current 10 A, 1000 mm Test Lead, Banana to Alligator, European Terminal, Max. Current 10 A, 1000 mm

GTL-303 RF Cable, for Trigger In/Out use FREE DOWNLOAD

PC Software, LabVIEW Driver





GTL-246

GRA-441-J

GRA-441-E



European Type Jack Terminal:

Rack Mount Kit for JIS type

Rack Mount Kit for EIA type



Specifications subject to change without notice. GPP-1000_E_ID1DH

Power Cord x 1, Packing List x 1, Test lead GTL-204A x 1

USB Cable (USB 2.0 A-B Type, approx. 1200 mm)