

# SPECIFICATIONS

Model	3310F		3311F		3312F	
Power	150W		300W		300W	
Current	30A		60A		12A	
Voltage	60V		60V		250V	
Min. Operating Voltage	0.6V @ 30A		0.6V @60A		1V @ 12A	
<b>Protections</b>						
Over Power Protection(OPP)	105%		105%		105%	
Over Current Protection(OCP)	105%		105%		105%	
Over Voltage Protection(OVP)	105%		105%		105%	
Over Temp Protection(OTP)	YES		YES		YES	
<b>Constant Current Mode</b>						
Range	0 ~ 3A	0 ~ 30A	0 ~ 6A	0 ~ 60A	0 ~ 1.2A	0 ~ 12A
Resolution	0.05mA	0.5mA	0.1mA	1mA	0.02mA	0.2mA
Accuracy	± 0.05% of ( setting + Range)					
<b>Constant Resistance Mode</b>						
Range	2 ~120KΩ	0.02Ω ~ 2Ω	1Ω ~ 60 KΩ	0.0083Ω ~ 1Ω	25Ω ~ 1500KΩ	0.08Ω ~ 25Ω
Resolution	0.00833mS	0.033mΩ	0.0166mS	0.0166mΩ	0.00066mS	0.4166mΩ
Accuracy	± 0.2% of (Setting + Range)					
<b>Constant Voltage Mode</b>						
Range	0 ~ 6V	0 ~ 60V	0 ~ 6V	0 ~ 60V	0 ~ 30V	0 ~ 250V
Resolution	0.0001V	0.001V	0.0001V	0.001V	0.001V	0.01V
Accuracy	± 0.025% of (Setting + Range)					
<b>Constant Power Mode</b>						
Range	0 ~ 15W	0 ~ 150W	0 ~ 30W	0 ~ 300W	0 ~ 30W	0 ~ 300W
Resolution	0.00025W	0.0025W	0.0005W	0.005W	0.0005W	0.005W
Accuracy	± 0.1% of (Setting + Range)					
<b>MPPT Mode</b>						
Algorithm	P & O					
Load mode	CV					
P&O interval	100ms ~ 6000ms					
<b>Dynamic Mode</b>						
<b>Timing</b>						
Thigh & Tlow	0.050~9.999 / 99.99 / 999.9 / 9999mS					
Resolution	0.001 / 0.01 / 0.1 / 1mS					
Slew rate	2.0 ~ 125mA/uS	20 ~ 1250mA/uS	4 ~ 250mA/uS	40 ~ 2500mA/uS	0.8 ~ 50mA/uS	8 ~ 500mA/uS
Accuracy	± (5% of Setting) ±10uS					
<b>Measurement</b>						
<b>Voltage Read Back</b>						
Range (5 Digital)	6V	60V	6V	60V	30V	250V
Resolution	0.0001V	0.001V	0.0001V	0.001V	0.001V	0.01V
Accuracy	± 0.025% of (Reading + Range)					
<b>Current Read Back</b>						
Range (5 Digital)	3A	30A	6A	60A	1.2A	12A
Resolution	0.0001A	0.001A	0.0001A	0.001A	0.00002A	0.0002A
Accuracy	± 0.05% of (Reading + Range)					
Current Monitor	FULL SCALE 10V					
Accuracy	0.5% of (Setting + Range)					
Current Programming Input	FULL SCALE 10V					
Programmable Short	BUILT-IN					
Load ON Voltage	0.1 ~ 25V		0.1 ~ 25V		0.2 ~ 50V	
Accuracy	1% of (Setting + Range)					
Load OFF Voltage	0 ~ 25V		0 ~ 25V		0 ~ 50V	
Accuracy	0.025% of (Setting + Range)					
Typical Short Resistance	0.02 Ω		0.0083 Ω		0.08 Ω	
Maximum Short Current	30 A		60 A		12 A	

Note: CC, CV, CP, and DAM accuracy improvements apply to firmware version R2.12 and later.

## SPECIFICATIONS

Model	3314F		3315F	
Power	300W		75W	
Current	12A		15A	
Voltage	500V		60V	
Min. Operating Voltage	6V @ 12A		0.3V @15A	
<b>Protections</b>				
Over Power Protection(OPP)	105%		105%	
Over Current Protection(OCP)	105%		105%	
Over Voltage Protection(OVP)	105%		105%	
Over Temp Protection(OTP)	YES		YES	
<b>Constant Current Mode</b>				
Range	0 ~ 1.2A	0 ~ 12A	0 ~ 1.5A	0 ~ 15A
Resolution	0.02mA	0.2mA	0.0254mA	0.25mA
Accuracy	± 0.05% of ( setting + Range)			
<b>Constant Resistance Mode</b>				
Range	50 ~ 3000KΩ	0.5Ω ~ 50Ω	4Ω ~ 240 KΩ	0.02Ω ~ 4Ω
Resolution	0.000333mS	0.8333mΩ	0.04166mS	0.0666mΩ
Accuracy	± 0.2% of (Setting + Range)			
<b>Constant Voltage Mode</b>				
Range	0 ~ 60V	0 ~ 500V	0 ~ 6V	0 ~ 60V
Resolution	0.001V	0.01V	0.0001V	0.001V
Accuracy	± 0.025% of (Setting + Range)			
<b>Constant Power Mode</b>				
Range	0 ~ 30W	0 ~ 300W	0 ~ 7.5W	0 ~ 75W
Resolution	0.001W	0.01W	0.000125W	0.00125W
Accuracy	± 0.1% of (Setting + Range)			
<b>MPPT Mode</b>				
Algorithm	P & O			
Load mode	CV			
P&O interval	1000ms ~ 60000ms			
<b>Dynamic Mode</b>				
<b>Timing</b>				
Thigh & Tlow	0.050~9.999 / 99.99 / 999.9 / 9999mS			
Resolution	0.001 / 0.01 / 0.1 / 1mS			
Slew rate	0.8 ~ 50mA/uS	8.0 ~ 500mA/uS	1 ~ 62.5mA/uS	10 ~ 625mA/uS
Accuracy	± (5% of Setting) ±10uS			
<b>Measurement</b>				
<b>Voltage Read Back</b>				
Range (5 Digital)	60V	600V	6V	60V
Resolution	0.001V	0.01V	0.0001V	0.001V
Accuracy	± 0.025% of (Reading + Range)			
<b>Current Read Back</b>				
Range (5 Digital)	1.2A	30A	1.5A	15A
Resolution	0.0001A	0.001A	0.00001A	0.001A
Accuracy	± 0.1% of (Reading + Range)			
Current Monitor	FULL SCALE 10V			
Accuracy	0.05% of (Setting + Range)			
Current Programming Input	FULL SCALE 10V			
Programmable Short	BUILT-IN			
Load ON Voltage	0.4 ~ 100V		0.1 ~ 25V	
Accuracy	1% of (Setting + Range)			
Load OFF Voltage	0 ~ 100V		0 ~ 25V	
Accuracy	0.025% of (Setting + Range)			
Typical Short Resistance	0.5 Ω		0.02Ω	
Maximum Short Current	12A		15A	

Note: CC, CV, CP, and DAM accuracy improvements apply to firmware version R2.12 and later.