

AFG-3051 & AFG-3081 Specifications

The specifications apply when the AFG-3051 & AFG-3081 is powered on for at least 30 minutes under +20°C~+30°C.

		AFG-3081	AFG-3051
Waveforms		Sine, Square, Ramp, Pulse, Noise, DC, Sin(x)/x, Exponential Rise, Exponential Fall, Negative Ramp	
Arbitrary Waveforms			
ARB Function		Built in	
Sample Rate		200 MSa/s	
Repetition Rate		100MHz	
Waveform Length		1M points	
Amplitude Resolution		16 bits	
Non-Volatile Memory		Ten 1M waveforms(1)	
User define Output Section		Any section from 2 to 1M points	
User define Mark Output		Any section from 2 to 1M points	
Frequency Characteristics			
Range	Sine	80MHz	50MHz
	Square		
	Triangle, Ramp	1MHz	
Resolution		1uHz	
Accuracy	Stability	±1 ppm 0 to 50°C	
		±0.3 ppm 18 to 28°C	
	Aging	±1 ppm, per 1 year	
	Tolerance	≤ 1 uHz	
Output Characteristics(2)			
Amplitude	Range	10 mVpp to 10 Vpp(into 50Ω) 20 mVpp to 20 Vpp(open-circuit)	
	Accuracy	± 1% of setting ±1 mVpp (at 1 kHz,>10 mVpp)	
	Resolution	0.1 mV or 4 digits	
	Flatness	± 1% (0.1dB) <10 MHz ± 2% (0.2 dB) 10 MHz to 50 MHz ± 10% (0.9 dB) 50 MHz to 70 MHz ± 20% (1.9 dB) 70 MHz to 80 MHz (sinewave relative to 1 kHz)	
	Units	Vpp, Vrms, dBm,	
Offset	Range	±5 Vpk ac +dc (into 50Ω) ±10Vpk ac +dc (Open circuit)	
	Accuracy	1% of setting + 2 mV+ 0.5% of amplitude	
Waveform Output	Impedance	50Ω typical (fixed) > 10MΩ (output disabled)	
	Protection	Short-circuit protected Overload relay auto-matically disables main output	
SYNC Output	Level	TTL-compatible into>1kΩ	
	Impedance	50Ω nominal	
Sinewave Characteristics			
Harmonic Distortion(5)		-60 dBc DC~1 MHz, Ampl < 3 Vpp -55 dBc DC~1 MHz, Ampl > 3 Vpp -45 dBc 1MHz~5 MHz, Ampl > 3 Vpp -30 dBc 5MHz~80 MHz, Ampl > 3 Vpp	
Total Harmonic Distortion		< 0.2%+0.1mVrms DC to 20 kHz	
Spurious (non-harmonic)(5)		-60 dBc DC~1 MHz	

	-50 dBc 1MHz~20MHz -50 dBc+ 6 dBc/octave 1MHz~80MHz
Phase Noise	< -65dBc typical 10MHz, 30 kHz band < -47dBc typical 80MHz, 30 kHz band
Square wave Characteristics	
Rise/Fall Time	<8 nS(3)
Overshoot	< 5%
Asymmetry	1% of period+1 ns
Variable Duty Cycle	20.0% to 80.0% ≤ 25 MHz 40.0% to 60.0% 25~50MHz 50.0%(Fixed) 50~80MHz
Jitter	0.01%+525ps < 2 MHz 0.1%+75ps > 2 MHz
Ramp Characteristics	
Linearity	< 0.1% of peak output
Variable Symmetry	0% to 100%
Pulse Characteristics	
Period	20ns~ 2000s
Pulse Width	8ns~ 1999.9s Minimum Pulse Width: 8nS when FREQ≤50MHz 5% of setting period when FREQ≤6.5MHz Resolution: 1nS when FREQ≤50MHz 1% of setting period when FREQ≤6.5MHz
Overshoot	<5%
Jitter	100 ppm +50 ps
AM Modulation	
Carrier Waveforms	Sine, Square, Triangle, Ramp, Pulse, Arb
Modulating Waveforms	Sine, Square, Triangle, Up/Dn Ramp
Modulating Frequency	2 MHz to 20 kHz
Depth	0% to 120.0%
Source	Internal / External
FM Modulation	
Carrier Waveforms	Sine, Square, Triangle, Ramp
Modulating Waveforms	Sine, Square, Triangle, Up/Dn Ramp
Modulating Frequency	2 MHz to 20 kHz
Peak Deviation	DC to 80 MHz
Source	Internal / External
PWM	
Carrier Waveforms	Square
Modulating Waveforms	Sine, Square, Triangle, Up/Dn Ramp
Modulating Frequency	2 MHz to 20 kHz
Deviation	0% ~ 100.0% of pulse width
Source	Internal / External
FSK	
Carrier Waveforms	Sine, Square, Triangle, Ramp, Pulse
Modulating Waveforms	50% duty cycle square
Internal Rate	2 MHz to 100 kHz
Frequency Range	DC to 80 MHz
Source	Internal / External
SWEEP	
Waveforms	Sine, Square, Triangle, Arb
Type	Linear or Logarithmic

Direction		Up or Down	
Start F / Stop FREQ		100 uHz to 80 MHz	100 uHz to 50 MHz
Sweep Time		1 ms to 500 s	
Trigger		Single, External, Internal	
Marker		Falling edge of Mark signal (Programmable frequency)	
Source		Internal / External	
BURST			
Waveforms		Sine, Square, Triangle, Ramp	
Frequency		1 uHz to 80 MHz(4)	1 uHz to 50 MHz(4)
Burst Count		1 to 1000000 cycles or Infinite	
Start / Stop Phase		-360.0° to +360.0°	
Internal Period		1 ms to 500 s	
Gate Source		External Trigger	
Trigger Source		Single, External or Internal Rate	
Trigger Delay		N-Cycle, Infinite: 0s to 85 s	
External Modulation Input			
Type		for AM, FM, Sweep, PWM	
Voltage Range		± 5V full scale	
Input Impedance		10kΩ	
Frequency		DC to 20 kHz	
External Trigger Input			
Type		for FSK, Burst, Sweep	
Input Level		TTL Compatible	
Slope		Rising or falling(selectable)	
Pulse Width		> 100 ns	
Input Impedance		10kΩ, DC coupled	
Latency	Sweep	< 10 us (typical)	
	Burst	< 100 ns (typical)	
Jitter	Sweep	2.5 us	
	Burst	1 ns; except pulse, 300 ps	
Modulation Output			
Type		for AM, FM, Sweep, PWM	
Amplitude	Range	≥ 1Vpp	
	Impedance	> 10kΩ typical (fixed)	
Trigger Output			
Type		for Burst, Sweep	
Level		TTL Compatible into 50Ω	
Pulse Width		> 450 ns	
Maximum Rate		1 MHz	
Fan-out		≥ 4 TTL load	
Impedance		50Ω typical	
Marker Output			
Type		for ARB, Sweep	
Level		TTL Compatible into 50Ω	
Fan-out		≥ 4 TTL load	
Impedance		50Ω typical	
Store/Recall		10 Groups of Setting Memories	
Interface		GPIB, RS232, USB	
Display		4.3 inch TFT LCD 480 × 3 (RGB) × 272	
System Characteristics			
Configuration Times (typical)		Function Change: Standard---->102ms	

	Pulse----->660ms Built-In Arb- >240ms Frequency Change: 24ms Amplitude Change: 50ms Offset Change: 50ms Select User Arb: < 2s for 1M points Modulation Change: < 200ms		
Arb Download Times (typical)	Binary Code		ASCII Code
	GPIB / RS-232 (115 Kbps)	USB(Device)	USB(Host)
1M points	189 Sec	34 Sec	70 Sec
512K points	95 Sec	18Sec	35 Sec
256K points	49 Sec	9 Sec	18 Sec
64K points	16 Sec	3 Sec	6 Sec
16K points	7 Sec	830mS	1340 mS
8K points	6 Sec	490mS	780mS
4K points	6 Sec	365mS	520 mS
2K points	5 Sec	300mS	390 mS
General Specifications			
Power Source	AC100~240V , 50~60Hz		
Power Consumption	65 VA		
Operating Environment	Temperature to satisfy the specification : 18 ~ 28°C Operating temperature : 0 ~ 40°C Relative Humidity: ≤ 80%, 0 ~ 40°C ≤ 70%, 35 ~ 40°C Installation category : CAT II		
Operating Altitude	2000 meters		
Pollution Degree	IEC 61010 Degree 2, Indoor Use		
Storage Temperature	-10 ~ 70°C, Humidity: ≤70%		
Dimensions (WxHxD)	Bench Top : 265 (W) x 107 (H) x 374 (D)		
Weight	Approx. 4kg		
Safety Designed to	EN61010-1		
EMC Tested to	EN 55011, IEC-61326-1		
Accessories	GTL-110× 1 Instruction Manual×1 Power cord×1		
<p>(1). A total of ten waveforms can be stored.(Every waveform can composed of 1M points maximum.)</p> <p>(2). Add 1/10th of output amplitude and offset specification per °C for operation outside of 0°C to 28°C range (1-year specification).</p> <p>(3). Edge time decreased at higher frequency.</p> <p>(4). Sine and square waveforms above 25 MHz are allowed only with an "Infinite" count.</p> <p>(5). Harmonic distortion and Spurious noise at low amplitudes is limited by a -70 dBm floor.</p>			