

Automatic Identification Measurement



GDM-9052 5 ½ Digit Dual Display Digital Multimeter

- * 5 ½ Digit Display: 239,999 Counts Max.
- * 4.3 TFT Graphic LCD & DCV Basic Accuracy: 0.012 %
- * A. I. Measurement Offers Automatic Identification and Measurement for Voltage, Resistance, Diode and Continuity Tests Without the Need for Manual Selection
- * 12 Different Measurement Functions: AC/DC Voltage, AC/DC Current, 2-wire/4-wire Resistance, Frequency, Period, Diode, Continuity, Capacitance and Temperature
- * True RMS (AC, AC+DC) Measurements
- * Dual Measurement Function to Providing Two Selected Measurement Simultaneously
- * Many Math Functions: Max./Min., REL/REL#, Compare, Hold, dB, dBm, MX+B, %, 1/X
- * Digital I/O Provides Dual Mode (Standard Compare and User Definition Modes)
- * Standard Interfaces: RS-232C and USB Device (Support USB CDC and USB TMC Modes)

SPECIFICATIONS (*1)

Range (*2)	Resolution	Input Resistance etc.	Accuracy (*3) 1 Year (23 °C ± 5 °C)
DC Voltage			
200.000 mV	1 μV	10 MΩ or > 10 GΩ	0.012 + 8
2.00000 V	10 μV	10 MΩ or > 10 GΩ	0.012 + 5
20.0000 V	100 μV	11.1 MΩ	0.012 + 5
200.000 V	1 mV	10.1 MΩ	0.012 + 5
1000.00 V	10 mV	10 MΩ	0.012 + 5
Resistance			
200.000 Ω	1 mΩ	1 mA	0.05 + 8
2.00000 kΩ	10 mΩ	1 mA	0.05 + 5
20.0000 kΩ	100 mΩ	100 μA	0.05 + 5
200.000 kΩ	1 Ω	10 μA	0.05 + 5
2.00000 MΩ	10 Ω	1 μA	0.05 + 5
10.0000 MΩ	100 Ω	0.5 μA	0.30 + 5
100.000 MΩ	1 kΩ	0.5 μA // 10 MΩ	3.00 + 8
DC Current			
20.0000 mA	100 nA	1 Ω	0.05 + 15
200.000 mA	1 μA	1 Ω	0.05 + 5
2.00000 A	10 μA	0.1 Ω	0.20 + 5
10.0000 A	100 μA	0.01 Ω	0.20 + 5
Continuity			
2000.00 Ω	10 mΩ	1 mA	0.05 + 5
Diode Test			
6.0000 V	100 μV	1 mA@ 6 V	0.05 + 15
Capacitance			
10.00 nF	0.01 nF	10 μA	2.0 + 10
100.0 nF	0.1 nF	10 μA	2.0 + 4
1.000 μF	0.001 μF	100 μA	2.0 + 4
10.00 μF	0.01 μF	1 mA	2.0 + 4
100.0 μF	0.1 μF	1 mA	2.0 + 4
True RMS AC (or AC+DC – AC Coupled) Voltage			
200.000 mV	1 μV	20 Hz to 45 Hz	1.0 + 100
		45 Hz to 10 kHz	0.3 + 100
		10 kHz to 30 kHz	1.5 + 300
		30 kHz to 100 kHz	5.0 + 300
2.00000 V	10 μV	20 Hz to 45 Hz	1.0 + 100
		45 Hz to 10 kHz	0.2 + 100
		10 kHz to 30 kHz	1.0 + 100
		30 kHz to 100 kHz	3.0 + 200
20.0000 V	100 μV	20 Hz to 45 Hz	1.0 + 100
		45 Hz to 10 kHz	0.2 + 100
		10 kHz to 30 kHz	1.0 + 100
		30 kHz to 100 kHz	3.0 + 200
200.000 V	1 mV	20 Hz to 45 Hz	1.0 + 100
		45 Hz to 10 kHz	0.2 + 100
		10 kHz to 30 kHz	1.0 + 100
		30 kHz to 100 kHz	3.0 + 200
750.00 V	10 mV	20 Hz to 45 Hz	1.0 + 100
		45 Hz to 10 kHz	0.2 + 100
		10 kHz to 30 kHz	1.0 + 100
		30 kHz to 100 kHz	3.0 + 200
True RMS AC (or AC+DC – AC Coupled) Current			
20.0000 mA	100 nA	20 Hz to 45 Hz	1.5 + 100
		45 Hz to 2 kHz	0.5 + 100
		2 kHz to 10 kHz	2.0 + 200
200.000 mA	1 μA	20 Hz to 45 Hz	1.5 + 100
		45 Hz to 2 kHz	0.5 + 100
		2 kHz to 10 kHz	2.0 + 200
2.00000 A	10 μA	20 Hz to 45 Hz	1.5 + 100
		45 Hz to 2 kHz	0.5 + 100
		2 kHz to 10 kHz	2.0 + 200
10.0000 A	100 μA	20 Hz to 45 Hz	1.5 + 100
		45 Hz to 2 kHz	1.0 + 100
		2 kHz to 10 kHz	-----

SPECIFICATIONS (*1)

Range (*2)	Resolution	Input Resistance etc.	Accuracy (*3) 1 Year (23 °C ± 5 °C)
Frequency			
(Voltage) 10 Hz to 1 MHz	-----	-----	0.01 + 3
(Current) 20 Hz to 10 kHz			
Temperature (Thermocouple)			
-200 °C to 0 °C	0.01 °C	J / T / K	0.6 °C (typical)
0 °C to +300 °C			0.3 °C (typical)
Display			
4.3" TFT Graphic LCD			
Interface			
RS-232C, USB device (USBCDC & USBTMC), Digital I/O			
Power Source			
AC 100 V / 120 V / 220 V / 240 V ± 10 %, 50 Hz to 60 Hz ; Power Consumption Max. 30 VA			
Dimensions & Weight			
268 (W) mm x 107 (H) mm x 302 (D) mm ; Approx. 3.2 kg			

Note: *1. All specifications are applicable to the single (1st) display only and warmed up for at least 30 minutes and operated in the slow rate.

*2. 20 % overrange on all ranges, except 750 V / 10 A range

*3. Accuracy: ± (% of Reading + Digits)

Specifications subject to change without notice.

GCM-9052GD1DS

ORDERING INFORMATION

GDM-9052 5 ½ Digit Dual Measurement Multimeter

ACCESSORIES :

Safety Instruction Sheet x 1, Power cord x 1, Test lead GTL-207A x 1

OPTIONAL ACCESSORIES

GTL-108A	4Wire Test Lead (Kelvin Clip), Approx. 1100 mm
GTL-205A	Temperature probe adaptor with thermocouple (K-type), Approx. 1000 mm
GTL-232	RS-232 Cable, 9 pin F-F type, null modem for computer, Approx. 2000 mm
GTL-246	USB Cable, A-B type, Approx. 1200 mm
GDM-TL1	Test Lead Set for All DMM
GSC-014	Soft Carrying Case for DMM Accessory
GRA-422	Rack Mount Kit (19" 2U)
GRA-454	Rack Mount Kit (19" 2U) for one set or two sets

Global Headquarters

GOOD WILL INSTRUMENT CO., LTD.

No.7-1, Jhongsing Road, Tucheng Dist., New Taipei City 236, Taiwan
T +886-2-2268-0389 F +886-2-2268-0639
E-mail: marketing@goodwill.com.tw

China Subsidiary

GOOD WILL INSTRUMENT (SUZHOU) CO., LTD.

No. 521, Zhujiang Road, Snd, Suzhou Jiangsu 215011 China
T +86-512-6661-7177 F +86-512-6661-7277

Malaysia Subsidiary

GOOD WILL INSTRUMENT (SEA) SDN. BHD.

No. 1-3-18, Elit Avenue, Jalan Mayang Pasir 3,
11950 Bayan Baru, Penang, Malaysia
T +604-6111122 F +604-6115225

Europe Subsidiary

GOOD WILL INSTRUMENT EURO B.V.

De Run 5427A, 5504DG Veldhoven, THE NETHERLANDS
T +31(0)40-2557790 F +31(0)40-2541194

U.S.A. Subsidiary

INSTEK AMERICA CORP.

5198 Brooks Street Montclair, CA 91763, U.S.A.
T +1-909-399-3535 F +1-909-399-0819

Japan Subsidiary

TEXIO TECHNOLOGY CORPORATION.

7F Towa Fudosan Shin Yokohama Bldg., 2-18-13 Shin
Yokohama, Kohoku-ku, Yokohama, Kanagawa,
222-0033 Japan
T +81-45-620-2305 F +81-45-534-7181

Korea Subsidiary

GOOD WILL INSTRUMENT KOREA CO., LTD.

Room No.503, Gyeonginro 775 (Mullae-Dong 3Ga,
Ace Hightech-City B/D 1Dong), Yeongduengpo-Gu,
Seoul 150093, Korea
T +82-2-3439-2205 F +82-2-3439-2207

India Subsidiary

GW INSTEK INDIA LLP.

2F, No. 20/1, Salarpuria Galleria Building, Bellary Road,
Kashi Nagar, Byatarayanapura, Bangalore, Karnataka 560092 India
T +91-80-4203-3235

GW INSTEK
Simply Reliable