

The SPS-Series are single output, 360W, switching DC power supply OVP protects the SPS-Series and their load from unexpected conditions. High regulation is maintained at 0.01%. Remote sensing adds extra level of precision by compensating cable losses between loads. Turning the output On/Off from external device is available through Remote control terminals. The GPS-Series are an ideal solution for power-efficient bench-top or portable applications requiring high regulation.

SPS-1230/1820/2415/3610/606





FEATURES

- * Dual Measurement Display
- * 0.01 % High Regulation
- * Constant Voltage and Constant Current
 Operation
- * High Efficiency
- * High Power Density
- * Over Voltage Protection
- * Remote Output ON/OFF Control

Rear Panel



SPECIFICATIONS						
OUTPUT						
	SPS-1230	SPS-1820	SPS-2415	SPS-3610	SPS-606	
Voltage	0 ~ 12V	0 ~ 18V	0 ~ 24V	0 ~ 36V	0 ~ 60V	
Current	0 ~ 30A	0 ~ 20A	0 ~ 15A	0 ~ 10A	0 ~ 6A	
CONSTANT VOLTAGE OPERATION						
Regulation	"	Line regulation ≤5mV				
	Load regulation	Load regulation ≤5mV				
Ripple & Noise	≤5mVrms, 10	≤5mVrms, 100mVp-p 20Hz ~ 20MHz				
Recovery Time	≤500μS	≤500μs				
	(50% Load ch	(50% Load change, Minimum load 0.5A)				
Temp. Coefficient	≤ 100ppm /°	≤ 100ppm /°C				
Output Range	0 to rating vol	0 to rating voltage continuously adjustable				
CONSTANT CURRENT OP	ERATION					
Regulation	Line regulation ≤3mA					
	Load regulation	Load regulation ≤3mA				
Ripple Current	≤3mArms (SF	≤3mArms (SPS-606)				
	≤5mArms (SF	≤5mArms (SPS-3610)				
	≤10mArms (S	≤10mArms (SPS-2415)				
	≤10mArms (S	≤10mArms (SPS-1820)				
	≤30mArms (S	≤30mArms (SPS-1230)				
Output Range	0 to rating current continuously adjustable					
	(HI/LO range	switchable)				
METER						
Туре	3 1/2 digit, 0.3	39" LED display				
Accuracy	± (0.5% of rdg	g + 2digits)				
INSULATION						
Chassis and Terminal	20MΩ or abov					
Chassis and AC Cord	30MΩ or abov	/e (DC 500V)				
POWER SOURCE						
AC 115V/ 230V ±15 %, 50/	60Hz					
DIMENSIONS & WEIGHT						
128(W) x 151(H) x 295(D) mm, Approx. 3.2kg						

DRDERING INFORMATION

	ORDERING INFORMATION				
SPS-1230	360W D.C. Switching Power Supply				
SPS-1820	360W D.C. Switching Power Supply				
SPS-2415	360W D.C. Switching Power Supply				
SPS-3610	360W D.C. Switching Power Supply				
SPS-606	360W D.C. Switching Power Supply				
ACCESSORIES :					
User manual x 1 , Power cord x 1					
Test lead GTL-203 x 1					