

PEL-3000H Specifications

The specifications apply when the PEL-3000H is powered on for at least 30 minutes under +20°C~+30°C.

PEL-3021H / PEL-3041H / PEL-3111H / PEL-3211H



Model		PEL-3021H	PEL-3041H	PEL-3111H	PEL-3211H	
Voltage		0V ~ 800V	0V ~ 800V	0V ~ 800V	0V ~ 800V	
Current		8.75A	17.5A	52.5A	105A	
Power		175W	350W	1050W	2100W	
Input Resistance		3.24MΩ	3.24MΩ	3.24MΩ	NA	
Min.Operating Voltage		5V at 8.75A	5V at 17.5A	5V at 52.5A	5V at 105A	
		2.5V at 4.375A	2.5V at 8.75A	2.5V at 26.25A	2.5V at 52.5A	
CC mode						
Operating Range	H	0A ~ 8.75A	0A ~ 17.5A	0A ~ 52.5A	0A ~ 105A	
	M	0A ~ 875mA	0A ~ 1.75A	0A ~ 5.25A	0A ~ 10.5A	
	L	0A ~ 87.5mA	0A ~ 175mA	0A ~ 525mA	0A ~ 1.05A	
Accuracy of Setting	H、M	$\pm (0.2\%set+0.1\%fs^{*1}) +Vin^{*2}/3.24M\Omega$				$\pm (1.2\%set+1.1\%fs)$
	L	$\pm (0.2\%set+0.1\%fs) +Vin^{*2}/3.24M\Omega$				$\pm (1.2\%set+1.1\%fs)$
Accuracy of Setting(Parallel)	H、M、L	$\pm (1.2\%set+1.1\%fs^{*3})$				$\pm (1.2\%set+1.1\%fs)$
Resolution	H	300μA	0.6mA	2mA	NA	

	M	30μA	60μA	200μA	NA
	L	3μA	6μA	20μA	NA
CR mode					
Operating Range	H	1.75S ~ 30μS (571mΩ ~ 33.3kΩ)	3.5S ~ 60μS (285mΩ ~ 16.6kΩ)	10.5S ~ 180μS (95.2mΩ ~ 5.55kΩ)	21S ~ 360μS(95.2mΩ ~ 2.777kΩ)
	M	175mS ~ 3μS (5.71Ω ~ 333MΩ)	350mS ~ 6μS (2.85mΩ ~ 166kΩ)	1.05S ~ 18μS (952mΩ ~ 55.5kΩ)	2.1S ~ 36μS(476mΩ ~ 27.77kΩ)
	L	17.5mS ~ 0.3μS (57.1Ω ~ 3.33MΩ)	35mS ~ 0.6μS (28.5mΩ ~ 1.66MΩ)	105mS ~ 1.8μS (9.52Ω ~ 555kΩ)	210mS ~ 3.6μS(4.762Ω ~ 277.7kΩ)
Accuracy of Setting	H、M	$\pm (0.5\%set+0.5\%fs^{*1}) +Vin^{*2}/3.24M\Omega$			$\pm (1.2\%set+1.1\%fs)$
	L	$\pm (0.5\%set+0.5\%fs) +Vin^{*2}/3.24M\Omega$			NA
	Parallel (TYP)	$\pm (1.2\%set+1.1\%fs^{*3})$			NA
Resolution	H	30μS	60μS	180 μS	NA
	M	3μS	6μS	18 μS	NA
	L	0.3μS	0.6μS	1.8 μS	NA
CV mode					
Operating Range	H	5V ~ 800V	5V ~ 800V	5V ~ 800V	5V ~ 800V
	L	5V ~ 80V	5V ~ 80V	5V ~ 80V	5V ~ 80V
Accuracy of Setting	H, L Range	$\pm (0.2\%set+0.2\%fs)$	$\pm (0.2\%set+0.2\%fs)$	$\pm (0.2\%set+0.2\%fs)$	$\pm (0.2\%set+0.2\%fs)$
	Parallel (TYP)	$\pm (0.2\%set+0.2\%fs)$	$\pm (0.2\%set+0.2\%fs)$	$\pm (0.2\%set+0.2\%fs)$	$\pm (0.2\%set+0.2\%fs)$
Resolution	H	20mV	20mV	20mV	NA
	L	2mV	2mV	2mV	NA
CP mode					
Operating Range	H	17.5W ~ 175W	35W ~ 350W	105W ~ 1050W	210W ~ 2100W
	M	1.75W ~ 17.5W	3.5W ~ 350W	10.5W ~ 105W	21W ~ 210W
	L	0.175W ~ 1.75W	0.35W ~ 10.5W	1.05W ~ 10.5W	2.1W ~ 21W
Accuracy of Setting	H、M	$\pm (0.6\%set+1.4\%fs) +Vin/3.24M\Omega$			$\pm (5\%fs)TYP$
Resolution	H	10mW	10mW	100mW	NA
	M	1mW	1mW	10mW	NA

		L	0.1mW	0.1mW	1mW	NA
Parallel mode						
Capacity			875W	1750W	5250W	PEL-3111H with 4 booster units: Max 9,45kW
Slew Rate						
Operation Mode			CC \ CR	CC \ CR	CC \ CR	NA
Setting Range	CC H		0.14mA/μs ~ 140mA/μs	0.280mA/μs ~ 280.0mA/μs	0.840mA/μs ~ 840mA/μs	NA
	CC M		0.014μA/μs ~ 14mA/μs	0.0280mA/μs ~ 28.00mA/μs	0.0840mA/μs ~ 84.00mA/μs	NA
	CC L		1.4μA/μs ~ 1400μA/μs	2.80μA/μs ~ 2800μA/μs	0.00840mA/μs ~ 8.400mA/μs	NA
	CR H		0.014mA/μs ~ 14mA/μs	0.0280mA/μs ~ 28.00mA/μs	0.0840mA/μs ~ 84.00mA/μs	NA
	CR M		0.0014mA/μs ~ 1.4mA/μs	0.00280mA/μs ~ 2.800mA/μs	0.00840mA/μs ~ 8.400mA/μs	NA
	CR L		0.14μA/μs ~ 140μA/μs	0.280μA/μs ~ 280.0μA/μs	0.000840mA/μs ~ 0.8400mA/μs	NA
Accuracy of Setting			± (10%set+25μs)	± (10%set+25μs)	± (10%set+25μs)	NA
Resolution			50μA/μs (14mA ~ 140mA/μs)	100μA/μs (28mA ~ 280mA/μs)	300μA/μs (84mA ~ 0.84A/μs)	NA
			5μA/μs (1.4mA ~ 14mA/μs)	10μA/μs (2.8mA ~ 28mA/μs)	30μA/μs (8.4mA ~ 84mA/μs)	NA
			0.5μA/μs (140μA ~ 1.4mA/μs)	1μA/μs (280μA ~ 2.8mA/μs)	3μA/μs (840μA ~ 8.4mA/μs)	NA
			50nA/μs (14μA ~ 140μA/μs)	0.1μA/μs (28μA ~ 280μA/μs)	0.3μA/μs (84μA ~ 840μA/μs)	NA
			5nA/μs (1.4μA ~ 14μA/μs)	10nA/μs (2.8μA ~ 28μA/μs)	30nA/μs (8.4μA ~ 84μA/μs)	NA
			0.5nA/μs (0.14μA ~ 1.4μA/μs)	1nA/μs (0.28μA ~ 2.8μA/μs)	3nA/μs (0.84μA ~ 8.4μA/μs)	NA
Meter						
Voltmeter	Accuracy		± (0.1%red+0.1%fs)	± (0.1%red+0.1%fs)	± (0.1%red+0.1%fs)	±(0.1%red+0.1%fs) TYP
Ammeter	Accuracy		± (0.2%red+0.3%fs)	± (0.2%red+0.3%fs)	± (0.2%red+0.3%fs)	NA
Ammeter	Parallel Accuracy TYP		± (1.2%red+1.1%fs)			±(1.2%red+1.1%fs) TYP
Dynamic mode						
Operation Mode			CC \ CR \ CP	CC \ CR \ CP	CC \ CR \ CP	NA
T1&T2			0.025ms ~ 10ms : 1μs	0.025ms ~ 10ms : 1μs	0.025ms ~ 10ms : 1μs	NA
			10ms ~ 60s : 1ms	10ms ~ 60s : 1ms	10ms ~ 60s : 1ms	NA

Accuracy		±100ppm of setting	±100ppm of setting	±100ppm of setting	±100ppm of setting
Slew Rate(CC)	H	0.140mA/us ~ 140.0mA	0.280mA/us ~ 280.0mA/us	0.840mA/us ~ 840.0mA/us	NA
	M	0.014mA/us ~ 14.00mA	0.028mA/us ~ 28.00mA/us	0.084mA/us ~ 84.00mA/us	NA
	L	1.400uA/us ~ 1400.0uA	2.800uA/us ~ 2800uA/us	0.0084mA/us ~ 8.400mA/us	NA
Slew Rate(CR)	H	0.014mA/us ~ 14.000mA	0.028mA/us ~ 28.00mA/us	0.084mA/us ~ 84.00mA/us	NA
	M	0.0014mA/us ~ 1.4000mA	0.028mA/us ~ 2.800mA/us	0.0084mA/us ~ 8.400mA/us	NA
	L	0.1400uA/us ~ 140.00uA	0.280uA/us ~ 280.0uA/us	0.00084mA/us ~ 0.8400mA/us	NA
Current Accuracy		±0.4%F.S			
PROTECTION FUNCTION					
Functions		Overvoltage protection(OVP), Overcurrent protection(OCP), Overpower protection(OPP), Overheat protection(OHP), Undervoltage protection(UVP), Reverse connection protection(REV)			
General					
Input Range		90VAC ~ 132VAC/ 180VAC ~ 250VAC Single-phase ; 47Hz~63Hz			
Power(Max.)		90VA	110VA	190VA	230VA
Interface		Std: USB, RS-232, Analog Control; Opt: GPIB			
Dimensions(mm) & Weight		213.8(W) x 124(H) x 400.5(D), Approx. 6kg	213.8(W) x 124(H) x 400.5(D), Approx. 7kg	427.8(W) x 124(H) x 400.5(D), Approx. 17kg	427.7(W) x 127.8(H) x 553.5(D), Approx. 23kg

PEL-3212H / PEL-3323H / PEL-3424H / PEL-3535H

Model		PEL-3212H	PEL-3323H	PEL-3424H	PEL-3535H
Operating voltage(DC)		0V~800V	0V~800V	0V~800V	0V~800V
Current		0~105A	0~157.5A	0~210A	0~262.5A
Power		2100W	3150W	4200W	5250W
Input Resistance		1.62MΩ	1.08MΩ	0.81MΩ	0.648MΩ
Min. Operating Voltage(DC)(Typ.)		5V at 105A 2.5V at 52.5A	5V at 157.5A 2.5V at 78.75A	5V at 210A 2.5V at 105A	5V at 262.5A 2.5V at 131.25A
CC mode					
Operating range	H	0A~105A	0~157.5A	0~210A	0~262.5A
	M	0A~10.5A	0A~15.75A	0~21A	0~26.25A
	L	0A~1.05A	0A~1.575A	0~2.1A	0~2.625A
Accuracy of setting	H,M	$\pm(0.2\% \text{ of set} + 0.1\% \text{ of f.s.}^{*1}) + V_{in}^{*2} / 3.24M\Omega^{*3}$			
	L	$\pm(0.2\% \text{ of set} + 0.1\% \text{ of f.s.}) + V_{in}^{*2} / 3.24 M\Omega$			
Resolution	H	4mA	6mA	8mA	10mA
	M	0.4mA	0.6mA	0.8mA	1mA
	L	0.04mA	0.06mA	0.08mA	0.1mA
CR mode					
Operating range ^{*4}	H	21S~360uS(47.619mΩ~2.778kΩ)	31.5S~540uS(31.746mΩ~1.85185kΩ)	42S~0.72mS(23.8095mΩ~1.3889kΩ)	52.5S~0.9mS(19.0476mΩ~1.1111kΩ)
	M	2.1S~36uS(476.19mΩ~27.778kΩ)	3.15S~540uS(317.46mΩ~18.5185kΩ)	4.2S~0.72mS(238.095mΩ~13.8889kΩ)	5.25S~0.9mS(190.476mΩ~11.1111kΩ)
	L	210mS~3.6uS(4.7619Ω~277.78kΩ)	315mS~540uS(3.1746Ω~185.185kΩ)	420mS~0.72mS(2.38095Ω~138.888kΩ)	525mS~0.9mS(1.90476Ω~111.111kΩ)
Accuracy of setting ^{*5}	H,M	$\pm(0.5\% \text{ of set}^{*6} + 0.5\% \text{ of f.s.}^{*1}) + V_{in}^{*2} / 3.24M\Omega$: Alone operation specifications			
	L	$\pm(0.5\% \text{ of set}^{*6} + 0.5\% \text{ of f.s.}) + V_{in}^{*2} / 3.24M\Omega$: Alone operation specifications			
Resolution	H	360uS	540uS	720uS	900uS
	M	36uS	54uS	72uS	90uS
	L	3.6uS	5.4uS	7.2uS	9uS
CV mode					

Operating range	H	5V~800V	5V~800V	5V~800V	5V~800V
	L	5V~80V	5V~80V	5V~80V	5V~80V
Accuracy of setting ^{*7}	H,L	$\pm(0.1\% \text{ of set} + 0.1\% \text{ of f.s})$			
Resolution	H	20mV			
	L	2mV			
CP mode					
Operating range	H	0W~2100W	0W~3150W	0W~4200W	0W~5250W
	M	0W~210W	0W~315W	0W~420W	0W~525W
	L	0W~21W	0W~31.5W	0W~42W	0W~52.5W
Accuracy of setting ^{*8}	H,M	$\pm(0.6\% \text{ of set} + 1.4\% \text{ of f.s}^{*3}) + V_{in} * V_{in}^{*3} / 3.24 \text{ M}\Omega$: Alone operation specifications			
	L	$\pm(0.6\% \text{ of set} + 1.4\% \text{ of f.s}) + V_{in} * V_{in}^{*3} / 3.24 \text{ M}\Omega$: Alone operation specifications			
Resolution	H	200mW	300mW	400mW	500mW
	M	20mW	30mW	40mW	50mW
	L	2mW	3mW	4mW	5mW
Slew rate					
Operation Mode		CC、CR	CC、CR	CC、CR	CC、CR
Setting range (CC mode)	H	1.68mA/us~840mA/us	2.52mA/us~839.7mA/us	3.36mA/us~840mA/us	4.2mA/us~840mA/us
	M	168uA/us~84mA/us	252uA/us~83.97mA/us	336uA/us~84mA/us	420uA/us~84mA/us
	L	16.8uA/us~8.4mA/us	25.2uA/us~8.397mA/us	33.6uA/us~8.4mA/us	42uA/us~8.4mA/us
Setting range (CR mode)	H	168uA/us~84mA/us	252uA/us~83.97mA/us	336uA/us~84mA/us	420uA/us~84mA/us
	M	16.8uA/us~8.4mA/us	25.2uA/us~8.397mA/us	33.6uA/us~8.4mA/us	42uA/us~8.4mA/us
	L	1.68uA/us~840uA/us	2.52uA/us~839.7uA/us	3.36uA/us~840uA/us	4.2uA/us~840uA/us
Accuracy of setting ^{*9}	$\pm(10\% \text{ of set} + 25\text{us})$				
Resolution	600uA(168mA/us~840mA/us)		900uA(252mA/us~839.7mA/us)		1.2mA(336mA/us~840mA/us)
Resolution	60uA(16.8mA/us~84mA/us)		90uA(25.2mA/us~83.97mA/us)		120uA(33.6mA/us~84mA/us)
Resolution	6uA(1.68mA/us~8.4mA/us)		9uA(2.52mA/us~8.3.97mA/us)		12uA(3.36mA/us~8.4mA/us)
Resolution	600nA(0.1680mA/us~84mA/us)		900nA(252nA/us~83.97mA/us)		1.2uA(336uA/us~84mA/us)
Resolution	60nA(0.01680mA/us~8.4mA/us)		90nA(25.2uA/us~8.397mA/us)		120nA(33.6uA/us~8.4mA/us)
Resolution	6nA(0.001680mA/us~0.84mA/us)		9nA(2.52uA/us~0.8397mA/us)		12nA(3.36uA/us~0.84mA/us)
Meter					
Voltmeter	Accuracy	$\pm(0.1\% \text{ of rdg} + 0.1\% \text{ of f.s})$			

Ammeter	Accuracy	±(1.2 % of rdg + 1.1 % of f.s)			
Dynamic mode					
Operation mode		CC and CR			
T1&T2		0.025ms ~ 10ms / Res : 1us			
		10ms ~ 30s / Res : 1ms			
Accuracy		1uS / 1mS ± 100ppm			
Slew Rate Setting range (CC mode)	H	1.68mA/us~840mA/us	2.52mA/us~839.7mA/us	3.36mA/us~840mA/us	4.2mA/us~840mA/us
	M	168uA/us~84mA/us	252uA/us~83.97mA/us	336uA/us~84mA/us	420uA/us~84mA/us
	L	16.8uA/us~8.4mA/us	25.2uA/us~8.397mA/us	33.6uA/us~8.4mA/us	42uA/us~8.4mA/us
Slew Rate Setting range (CR mode)	H	168uA/us~84mA/us	252uA/us~83.97mA/us	336uA/us~84mA/us	420uA/us~84mA/us
	M	16.8uA/us~8.4mA/us	25.2uA/us~8.397mA/us	33.6uA/us~8.4mA/us	42uA/us~8.4mA/us
	L	1.68uA/us~840uA/us	2.52uA/us~839.7uA/us	3.36uA/us~840uA/us	4.2uA/us~840uA/us
Current Accuracy		±0.4%F.S.			
PROTECTION FUNCTION					
Functions		Overvoltage protection(OVP), Overcurrent protection(OCP), Overpower protection(OPP), Overheat protection(OHP), Undervoltage protection(UVP), Reverse connection protection(REV)			
General					
Input Range		90VAC ~ 132VAC/ 180VAC ~ 250VAC Single-phase ; 47Hz~63Hz			
Power(Max.)		380VA	570VA	760VA	950VA
Interface		Std: USB, RS-232, Analog Control; Opt: GPIB			
Dimensions(mm) & Weight		598(W) x 611(H) x 706(D), Approx. 67.5kg	598(W) x 611(H) x 706(D), Approx. 85.5kg	598(W) x 877(H) x 706(D), Approx. 110kg	598(W) x 877(H) x 706(D), Approx. 127.5kg

PEL-3322H / PEL-3533H / PEL-3744H / PEL-3955H

Model		PEL-3322H	PEL-3533H	PEL-3744H	PEL-3955H
Operating voltage(DC)		0V~800V	0V~800V	0V~800V	0V~800V
Current		0~157.5A	0~262.5A	0~367.5A	0~472.5A
Power		3150W	5250W	7350W	9450W
Input Resistance		3.24MΩ	3.24MΩ	3.24MΩ	3.24MΩ
Min. Operating Voltage(DC)(Typ.)		5V at 157.5A 2.5V at 78.75A	5V at 262.5A 2.5V at 131.25A	5V at 367.5A 2.5V at 183.75A	5V at 472.5A 2.5V at 236.25A
CC mode					
Operating range	H	0~157.5A	0~262.5A	0~367.5A	0~472.5A
	M	0~15.75A	0~26.25A	0~36.75A	0~47.25A
	L	0~1.575A	0~2.625A	0~3.675A	0~4.725A
Accuracy of setting	H,M	$\pm(1.2\% \text{ of set} + 1.1\% \text{ of f.s.}^{*1}) + V_{in}^{*2}/3.24\text{M}\Omega^{*3}$			
	L	$\pm(1.2\% \text{ of set} + 1.1\% \text{ of f.s.}) + V_{in}^{*2}/3.24\text{M}\Omega$			
Resolution	H	6mA	10mA	14mA	18mA
	M	0.6mA	1mA	1.4mA	1.8mA
	L	0.06mA	0.1mA	0.14mA	0.18mA
CR mode					
Operating range ^{*4}	H	31.5S~540uS(31.746mΩ~1.85185kΩ)	52.5S~0.9mS(19.0476mΩ~1.11111kΩ)	73.5S~1.26mS(13.6054mΩ~793.651Ω)	94.5S~1.26mS(10.582mΩ~617.284Ω)
	M	3.15S~540uS(317.46mΩ~18.5185kΩ)	5.25S~0.9mS(190.476mΩ~11.1111kΩ)	7.35S~126uS(136.054mΩ~7.93651kΩ)	9.45S~126uS(105.82mΩ~6.17284kΩ)
	L	315mS~540uS(3.1746Ω~185.185kΩ)	525mS~0.9mS(1.90476Ω~111.111kΩ)	735mS~12.6uS(1.36054Ω~79.3651kΩ)	945mS~162uS(1.0582Ω~61.7284kΩ)
Accuracy of setting ^{*5}	H,M	$\pm(0.5\% \text{ of set}^{*6} + 0.5\% \text{ of f.s.}^{*1}) + V_{in}^{*2}/3.24\text{M}\Omega$: Alone operation specifications			
	L	$\pm(0.5\% \text{ of set}^{*6} + 0.5\% \text{ of f.s.}) + V_{in}^{*2}/3.24\text{M}\Omega$: Alone operation specifications			
Resolution	H	540uS	900uS	1.26mS	1.62mS
	M	54uS	90uS	126uS	162uS
	L	5.4uS	9uS	12.6uS	16.2uS
CV mode					
Operating range	H	5V~800V	5V~800V	5V~800V	5V~800V
	L	5V~80V	5V~80V	5V~80V	5V~80V

Accuracy of setting ^{*7}	H,L	±(0.1 % of set + 0.1 % of f.s)			
Resolution	H	20mV			
	L	2mV			
CP mode					
Operating range	H	0W~3150W	0W~5250W	0W~7350W	0W~9450W
	M	0W~315W	0W~525W	0W~735W	0W~945W
	L	0W~31.5W	0W~52.5W	0W~73.5W	0W~94.5W
Accuracy of setting ^{*8}	H,M	±(0.6 % of set + 1.4 % of f.s ^{*3}) + Vin*Vin ^{*3} /3.24MΩ : Alone operation specifications			
	L	±(0.6 % of set + 1.4 % of f.s) + Vin*Vin ^{*3} /3.24MΩ : Alone operation specifications			
Resolution	H	300mW	500mW	700mW	900mW
	M	30mW	50mW	70mW	90mW
	L	3mW	5mW	7mW	9mW
Slew rate					
Operation Mode		CC、CR	CC、CR	CC、CR	CC、CR
Setting range (CC mode)	H	2.52mA/us~839.7mA/us	4.2mA/us~840mA/us	5.88mA/us~840mA/us	7.56mA/us~839.7mA/us
	M	252uA/us~83.97mA/us	420uA/us~84mA/us	588uA/us~84mA/us	756uA/us~83.97mA/us
	L	25.2uA/us~8.397mA/us	42uA/us~8.4mA/us	58.8uA/us~8.4mA/us	75.6uA/us~8.397mA/us
Setting range (CR mode)	H	252uA/us~83.97mA/us	420uA/us~84mA/us	588uA/us~84mA/us	756uA/us~83.97mA/us
	M	25.2uA/us~8.397mA/us	42uA/us~8.4mA/us	58.8uA/us~8.4mA/us	75.6uA/us~8.397mA/us
	L	2.52uA/us~839.7uA/us	4.2uA/us~840uA/us	5.88uA/us~840uA/us	7.56uA/us~839.7uA/us
Accuracy of setting ^{*9}	±(10% of set + 25us)				
Resolution	900uA(252mA/us~839.7mA/us)		1.5mA(420mA/us~840mA/us)		2.1mA(588mA/us~840A/us)
Resolution	90uA(25.2mA/us~83.97mA/us)		150uA(42mA/us~84mA/us)		210uA(58.8mA/us~84mA/us)
Resolution	9uA(2.52mA/us~8.397mA/us)		15uA(4.2mA/us~8.4mA/us)		21uA(5.88mA/us~8.4mA/us)
Resolution	900nA(252nA/us~83.97mA/us)		1.5uA(420uA/us~84mA/us)		2.1uA(588uA/us~84mA/us)
Resolution	90nA(25.2uA/us~8.397mA/us)		150nA(42uA/us~8.4mA/us)		210nA(58.8uA/us~8.4mA/us)
Resolution	9nA(2.52uA/us~0.8397mA/us)		15nA(4.2uA/us~0.84mA/us)		21nA(5.88uA/us~0.84mA/us)
Meter					
Voltmeter	Accuracy	±(0.1 % of rdg + 0.1 % of f.s)			
Ammeter	Accuracy	±(1.2 % of rdg + 1.1 % of f.s)			
Dynamic mode					
Operation mode		CC and CR			
T1&T2		0.025ms ~ 10ms / Res : 1us			

		10ms ~ 30s / Res : 1ms			
Accuracy		1uS / 1mS ± 100ppm			
Slew Rate	H	2.52mA/us~839.7mA/us	4.2mA/us~840mA/us	5.88mA/us~840mA/us	7.56mA/us~839.7mA/us
	M	252uA/us~83.97mA/us	420uA/us~84mA/us	588uA/us~84mA/us	756uA/us~83.97mA/us
Setting range (CC mode)	L	25.2uA/us~8.397mA/us	42uA/us~8.4mA/us	58.8uA/us~8.4mA/us	75.6uA/us~8.397mA/us
	H	252uA/us~83.97mA/us	420uA/us~84mA/us	588uA/us~84mA/us	756uA/us~83.97mA/us
Slew Rate	M	25.2uA/us~8.397mA/us	42uA/us~8.4mA/us	58.8uA/us~8.4mA/us	75.6uA/us~8.397mA/us
	L	2.52uA/us~839.7uA/us	4.2uA/us~840uA/us	5.88uA/us~840uA/us	7.56uA/us~839.7uA/us
Setting range (CR mode)					
Current Accuracy		±0.4%F.S.			
PROTECTION FUNCTION					
Functions		Overvoltage protection(OVP), Overcurrent protection(OCP), Overpower protection(OPP), Overheat protection(OHP), Undervoltage protection(UVP), Reverse connection protection(REV)			
General					
Input Range		90VAC ~ 132VAC/ 180VAC ~ 250VAC Single-phase ; 47Hz~63Hz			
Power(Max.)		420VA	650VA	880VA	1110VA
Interface		Std: USB, RS-232, Analog Control; Opt: GPIB			
Dimensions(mm) & Weight		598(W) x 611(H) x 706(D), Approx. 73kg	598(W) x 611(H) x 706(D), Approx. 96.5kg	598(W) x 877(H) x 706(D), Approx. 125kg	598(W) x 877(H) x 706(D), Approx. 149kg

*1 Full scale of H range

*2 V_{in} : input terminal voltage of electronic load

*3 M range applies to the full scale of H range

*4 $Siemens[S] = Input\ current[A] / Input\ voltage[V] = 1 / resistance[\Omega]$

*5 Converted value at the input current. At the input current. It is not applied for the condition of the parrallel operation.

*6 $set = V_{in} / R_{set}$

*7 At the sensing point during remote sensing under the operating range of the input voltage. It is also applied for the condition of the parrallel operation.

*8 It is not applied for the condition of the parrallel operation.

*9 Time to reach from 10 % to 90 % when the current is varied from 2 % to 100 % (20 % to 100 % in M range) of the rated current.