

Specifications							
Range	Shunt Value	*DC Accuracy		*AC Accuracy ≤ 400Hz		Max input DC/AC rms	Output Voltage
		Typ.	Max.				
1000 A	0.0001 Ω	0.02 % of Reading + 0.01 % of Range	0.05 % of Reading + 0.05 % of Range	50 Hz to 200 Hz	0.1 % (Reading + Range)	1000 A	1000 A / 0.1 V
				201 Hz to 300 Hz	0.2 % (Reading + Range)		
				301 Hz to 400 Hz	0.4 % (Reading + Range)		
200 A	0.001 Ω	0.02 % of Reading	0.04 % of Reading	0.10 % of Reading		250 A	200 A / 0.2 V
20 A	0.01 Ω	0.01 % of Reading	0.02 % of Reading	0.10 % of Reading		30 A	20 A / 0.2 V
2 A	0.1 Ω	0.01 % of Reading	0.02 % of Reading	0.10 % of Reading		4 A	2 A / 0.2 V
0.2 A	1 Ω	0.01 % of Reading	0.02 % of Reading	0.10 % of Reading		0.4 A	0.2 A / 0.2 V

5 1/2 Digit Ampere Meter					
Range	Resolution	*DC		*AC(50 Hz to 400 Hz)	
		Accuracy ± (% of reading + of Range)			
		Typ.	Max.		
1000 A	0.01 A	0.04+0.02	0.1+0.05	50 to 200 Hz	0.5+0.1
				201 to 300 Hz	0.5+0.2
				301 to 400 Hz	0.5+0.4
200 A	0.001 A / 0.01A	0.04+0.01	0.08+0.01	0.5+0.05	
20 A	0.0001 A / 0.001 A	0.02+0.01	0.04+0.01	0.5+0.05	
2 A	0.01 mA / 0.1 mA	0.02+0.01	0.04+0.01	0.5+0.05	
0.2 A	0.001 mA / 0.01 mA	0.02+0.01	0.04+0.01	0.5+0.05	

*AC accuracy is limited to 100 A.

*AC input : Range 0.2 A, 2 A, 20 A, 200 A ≥ 5 % of Range

Range 1000 A ≥ 10 % of Range

*The specifications apply when the 1000 A is powered on for at least 30 minutes

*The typical not apply when 20 A, 200 A, 1000 A use over 50 % range current and over 3 mins or the ON/OFF current period ratio less than 1/3.

*For high accuracy measurement please use the 6 1/2 D.V.M. to measure the voltage output which is proportional to the current value and suggest 6 1/2 D.V.M. away from shunt at least 120cm.

General information's :	
Temperature range :	0 °C to 40 °C; stated accuracy for 1 year at 23 °C±2 °C.
Temperature coefficient :	Range 0.2 A 、 2 A Less than 0.001 % per °C (20 °C to 40 °C)
	Range 20 A Less than 0.002 % per °C (20 °C to 40 °C)
	Range 200 A Less than 0.003 % per °C (20 °C to 40 °C)
	Range 1000 A Less than 0.005 % per °C (20 °C to 40 °C)

AC INPUT	LINE	115 Vac/ 230 Vac ± 10 %
	FREQUENCY	50/60 Hz
	MAX. POWER CONSUMPTION	25W
Dimension(HxWxD)	89 mm x 440 mm x 370 mm	
WEIGHT	13.5Kg	