

SPECIFICATIONS

Model	36250A		36260A		36350A		36360A	
Power	50 KW	50 KW	60 KW	60 KW	50 KW	50 KW	60 KW	60 KW
Current	0 A to 21 A	0 A to 210 A	0 A to 24 A	0 A to 240 A	0 A to 50 A	0 A to 500 A	0 A to 60 A	0 A to 600 A
Voltage	0 V to 600 V				0 V to 1000 V			
Min. Operating Voltage	20 V @ 210 A		20 V @ 240 A		30 V @ 500 A		30 V @ 600 A	
Protections								
Over Power Protection(OPP)					105 %			
Over Current Protection(OCF)					104 %			
Over Voltage Protection(OVP)					105 %			
Over Temp Protection(OTP)					YES			
Constant Current Mode								
Range *1	21 A	210 A	24 A	240 A	5.00 A	500 A	60 A	600 A
Resolution	0.336 mA	3.36 mA	0.384 mA	3.84 mA	0.875 mA	8.75 mA	1 mA	10 mA
Accuracy	± 0.05 % of (Setting + Range)							
Constant Resistance Mode								
Range	8571 Ω to 2.857 Ω	2.857 Ω to 0.0477 Ω	7500 Ω to 2.5 Ω	2.5 Ω to 0.0417 Ω	2280 Ω to 1.9 Ω	1.9 Ω to 0.02 Ω	2000 Ω to 1.666 Ω	1.666 Ω to 0.01668 Ω
Resolution*6	5.83 μS	47.7 μΩ	6.66 μS	41.7 μΩ	8.7 μS	32 μΩ	10 μS	27.833 μΩ
Accuracy	± 0.2 % of (Setting + Range)							
Constant Voltage Mode								
Range	0 V to 600 V				10 V to 1000 V			
Resolution	10 mV				16 mV			
Accuracy	± 0.05 % of (Setting + Range)							
Constant Power Mode								
Range	5 KW	50 KW	6 KW	60 KW	5 KW	50 KW	6 KW	60 KW
Resolution	0.0875 W	0.875 W	0.1 W	1 W	0.0875 W	0.875 W	0.1 W	1 W
Accuracy *2	± 0.1 % of (Setting + Range)							
Constant Voltage + Current Limit Mode								
Range	600 V	210 A	600 V	240 A	1000 V	500 A	1000 V	600 A
Resolution	10 mV	3.36 mA	10 mV	3.84 mA	16 mV	8.75 mA	16 mV	10 mA
Accuracy	± 0.05 % of (Setting + Range) ± 1.0 % of (Setting + Range) ± 0.05 % of (Setting + Range) ± 1.0 % of (Setting + Range) ± 0.05 % of (Setting + Range) ± 1.0 % of (Setting + Range) ± 0.05 % of (Setting + Range) ± 1.0 % of (Setting + Range)							
Constant Voltage + Power Limit Mode								
Range	600 V	50 KW	600 V	60 KW	1000 V	50 KW	1000 V	60 KW
Resolution	10 mV	0.875 W	10 mV	1 W	16 mV	0.8 W	16 mV	1 W
Accuracy	± 0.05 % of (Setting + Range) ± 1.0 % of (Setting + Range) ± 0.05 % of (Setting + Range) ± 1.0 % of (Setting + Range) ± 0.05 % of (Setting + Range) ± 1.0 % of (Setting + Range) ± 0.05 % of (Setting + Range) ± 1.0 % of (Setting + Range)							
MPPT Mode								
Algorithm	P & O							
Load mode	CV							
P&O interval	1000 ms to 60000 ms ; resolution 1000 ms							
Dynamic Mode								
Timing	0.050 ms to 9.999 ms / 99.99 ms / 999.9 ms / 9999 ms							
Thigh & Tlow	0.001 ms / 0.01 ms / 0.1 ms / 1 ms							
Resolution	1 μs / 10 μs / 100 μs / 1 ms + 50 ppm							
Accuracy	1 μs / 10 μs / 100 μs / 1 ms + 50 ppm							
Slew rate	6.8m A/μs to 1.05 A/μs	68 mA/μs to 10.5 A/μs	9.2 mA/μs to 1.2 A/μs	192 mA/μs to 12 A/μs	0.04 A/μs to 2.5 A/μs	0.4 A/μs to 25 A/μs	0.048 A/μs to 3 A/μs	0.48 A/μs to 30 A/μs
Resolution	4.2 mA/μs	42 mA/μs	4.8 mA/μs	48 mA/μs	0.01 A/μs	0.1 A/μs	0.012 A/μs	0.12 A/μs
Min. Rise Time	20 μs (typical)							
Accuracy	± (5 % of Setting) ± 10 μs							
Current	0 A to 21 A	21 A to 210 A	0 A to 24 A	24 A to 240 A	0 A to 50 A	50 A to 500 A	0 A to 60 A	60 A to 600 A
Resolution	0.336 mA	3.36 mA	0.384 mA	3.84 mA	0.875 mA	8.75 mA	1 mA	10 mA
Measurement								
Voltage Read Back								
Range (5 Digital)	0 V to 60 V	60 V to 600 V	0 V to 60 V	60 V to 600 V	0 V to 100 V	100 V to 1000 V	0 V to 100 V	100 V to 1000 V
Resolution	1 mV	10 mV	1 mV	10 mV	1.6 mV	16 mV	1.6 mV	16 mV
Accuracy	± 0.025 % of (Reading + Range)							
Current Read Back								
Range (5 Digital)	0 A to 21 A	21 A to 210 A	0 A to 24 A	24 A to 240 A	0 A to 50 A	50 A to 500 A	0 A to 60 A	60 A to 600 A
Resolution	0.336 mA	3.36 mA	0.384 mA	3.84 mA	0.875 mA	8.75 mA	1 mA	10 mA
Accuracy	± 0.05 % of (Reading + Range)							
Power Read Back								
Range (5 Digital)	5 KW	50 KW	6 KW	60 KW	5 KW	50 KW	6 KW	60 KW
Resolution	0.1 W	1 W	0.1 W	1 W	0.1 W	1 W	0.1 W	1 W
Accuracy *3	± 0.0 6% of (Reading + Range)							
General								
Short Circuit								
Current	210 A		240 A		500 A		600 A	
Load ON Voltage	0.4 V to 100 V		0.4~ 100V		10.4 V to 200 V		10.4 V to 200 V	
Load OFF Voltage	0 V to 99 V		0 ~ 99V		0 V to 198.4 V		0 V to 198.4 V	
Operating Range								
Temperature *4	0 °C to 40 °C							
Humidity	20 % to 85 %rh							
Storage Range								
Temperature	-20 °C to +70 °C							
Humidity	<= 90 %rh							
Withstanding voltage test								
AC input and FG	AC 1500 V, 1 minute.							
AC input and Load terminal	AC 3000 V, 1 minute.							
Load terminal and FG	AC 1500 V, 1 minute.							
Safety & EMC	CE							

Note *1 : The range is automatically or forcing to range II only in CC mode

Note *2 : If the operating voltage is higher than 600 V, the accuracy specification is 0.5 % F.S.

Note *3 : Power F.S. = Vrange F.S. x Irange F.S.

Note *4: Operating temperature range is 0 °C to 40 °C, All specifications apply for 25 °C±5 °C, Except as noted

Note *5: 1000 V Model Specifications apply only for load input voltage > 50 V

Note *6 : μS (microsiemens) is the unit of conductance(G), one siemens equal to 1/Ω

Input AC Power : 100 Vac to 230 Vac ± 10 %, 50/60 Hz

Cooling : Advanced Fan Cooled

All specifications are subject to change without notice.

