

Digital Clamp Meter

**GCM-403****FEATURES**

- * AC/DC 600A/600V Max Input
- * Auto Range Except Current Measurement
- * Auto Power Off
- * Capacitance Measurement
- * Frequency Measurement
- * Temperature Measurement
- * Max. Clamp Size : Ø 28mm

SPECIFICATIONS	
ACV	
Range	4V, 40V, 400V, 600V
Resolution	0.001V, 0.01V, 0.1V, 1V
Accuracy	$\pm(1.0 + 5) \sim \pm(1.2 + 5)$
Input Impedance	$\geq 10M\Omega$ // $100pF$ at least
Frequency Response	40~400Hz
ACA	
Range	40A, 600A
Resolution	0.01A, 1A
Accuracy	$\pm(2.5 + 5) \sim \pm(2.5 + 8)$
Frequency Response	50~60Hz
DCV	
Range	400mV, 4V, 40V, 400V, 600V
Resolution	0.1mV, 0.001V, 0.01V, 0.1V, 1V
Accuracy	$\pm(0.8 + 1) \sim \pm(1.0 + 3)$
Input Impedance	$\geq 10M\Omega$
DCA	
Range	40A, 600A
Resolution	0.01A, 1A
Accuracy	$\pm(2.0 + 5)$
OHM	
Range	400Ω, 4kΩ, 40kΩ, 400kΩ, 4MΩ, 40MΩ
Resolution	0.1Ω, 0.001kΩ, 0.01kΩ, 0.1kΩ, 0.001MΩ, 0.01MΩ
Accuracy	$\pm(1.0 + 2) \sim \pm(1.5 + 2)$
DIODE	
Range	4V
Resolution	0.001V
Open-circuit Voltage	Approx. 1.48V
CONTINUITY	
Range	400Ω
Resolution	0.1Ω
Accuracy	The buzzer turns on for resistance lower than 10Ω
Open-circuit Voltage	Approx. 0.45V
CAPACITANCE	
Range	40nF, 400nF, 4μF, 40μF, 100μF
Resolution	0.01nF, 0.1nF, 0.001μF, 0.01μF, 0.1μF
Accuracy	$\pm(4.0 + 3) \sim \pm(5.0 + 10)$
FREQUENCY	
Range	10Hz, 100Hz, 1kHz, 10kHz, 100kHz, 1MHz, 10MHz
Resolution	0.001Hz, 0.01Hz, 0.1Hz, 1Hz, 10Hz, 100Hz, 1kHz
Accuracy	$\pm(4.0 + 3) \sim \pm(5.0 + 10)$
TEMPERATURE (°C only)	
Range	-40°C ~ 1000°C
Accuracy	$\pm(2.5 + 3) \sim \pm(8.0 + 5)$
OTHER FUNCTION	
Data Hold, REL	
LCD DISPLAY	
Liquid crystal display : Displays 4000 counts maximum.	
CLAMP OPENING DIAMETER	
Ø 28mm Maximum	
POWER SOURCE	
9V battery (16F22)	
DIMENSIONS & WEIGHT	
210 (L) x 76 (W) x 30 (H) mm; Approx. 260g	

ORDERING INFORMATION**GCM-403** Digital Clamp Meter**ACCESSORIES :**

User manual x 1, Test leads, Temperature probe, Carrying case