Programmable Switching D.C. Power Supply



PSP-603/405/2010



FEATURES

- * LCD Display
- * Output ON/OFF Control
- * 3 Step Fan Speed Control
- * Voltage/Current/Power Setting
- * Key Lock to Avoid Error Operation
- \ast Normal , +% & -% Output Operation Key
- * Standard Interface : RS-232C
- * Optional European Type Jack Terminal

The PSP-Series is single output, 200W, programmable switching DC power supplies. OVL, OCL, OTP,
and OPL protect the PSP-Series and its loads from unexpected conditions. The PSP-Series has a large
LCD panel with output and parameter views and a key lock feature to prevent changing the settings.
The PSP-Series is suitable for generic bench-top applications in laboratories and educational
institutions.

Model	PSP-603	PSP-405	PSP-2010
Voltage	0 ~ 60V	0 ~ 40V	0 ~ 20V
Current	0 ~ 3.5A	0~5A	0~10A
VOLTAGE REGULATION		<u> </u>	1
Load	< 10mV	< 10mV	< 10mV
Line	$\stackrel{\leq}{=}$ 10mV $\stackrel{\leq}{=}$ 0.05%	\leq 10mV \leq 0.05%	$ \stackrel{\leq}{=} 10 \text{mV} \\ \stackrel{\leq}{=} 0.05\% $
CURRENT REGULATION		<u> </u>	
Load	\leq 5mA	< 5mA	< 5mA
Line	$\leq 0.05\%$	$\leq 0.05\%$	$\leq 0.05\%$
RIPPLE			
Voltage (mVrms)	5 20-14	5 20	5 20
Current (mArms)	$\stackrel{\leq}{=} 20 mV$ $\stackrel{\leq}{=} 10 mA$	$\leq 20 mV$ $\leq 10 mA$	$\leq 20 \text{mV}$ $\leq 10 \text{mA}$
. ,	_ TUMA	_ 10mA	
RESOLUTION			1
Voltage Current	20mV	10mV	10mV
	2mA	2mA	5mA
PROGRAM ACCURACY			
Voltage	<u>+</u> 0.05%rdg <u>+</u> 4digits	<u>+</u> 0.05%rdg <u>+</u> 3digits	<u>+</u> 0.05%rdg <u>+</u> 3digits
Current	<u>+</u> 0.1%rdg + 5digits	\pm 0.1%rdg + 5digits	<u>+</u> 0.3%rdg + 10digits
READBACK (METER) RESOL		-	1
Voltage	Same as Resolution	Same as Resolution Same as Resolution	Same as Resolution
Current READBACK (METER) ACCUR		Same as Resolution	Same as Resolution
Voltage	Same as Program Accuracy	Same as Program Accuracy	Same as Program Accura
Current	Same as Program Accuracy	Same as Program Accuracy	Same as Program Accura
PROTECTION			
OVL/OCL/OPL/OTP	V	V	V
OUTPUT ON/OFF CONTR	ROL		
	V	\vee	V
DISPLAY			
LCD			
INTERFACE (STANDARD)			
RS-232C			
POWER SOURCE			
AC 115V <u>+</u> 10% , AC 230V <u>+</u> 1	5%, 50/60Hz		
DIMENSIONS & WEIGHT			

	ORDERING INFORMATION		
PSP-603 PSP-405 PSP-2010	200W Programmable Switching DC Power Supply 200W Programmable Switching DC Power Supply 200W Programmable Switching DC Power Supply		
ACCESSORIES : User manual x 1, Power cord x 1, Test lead GTL-104A x 1 , European test lead GTL-204A x 1			
OPTIONAL ACCESSORIES			
	RS-232C Cable Rack Mount Kit, 19", 3U Size		
FREE DO	WNLOAD		
PC Softwar	re RS-232C Remote Control Software		

European Type Jack Terminal



Rear Panel

No. 1997
CE