

		GPP-3610H	GPP-7250
OUTPUT MODE			
Number of Channel	CH1	CH1	
Voltage	0 ~ 36.000V	0 ~ 72.000V	
Current	0 ~ 10.0000A	0 ~ 5.0000A	
Constant Voltage Operation			
Line Regulation	≤ 0.01% + 3mV		
Load Regulation	≤ 0.01% + 5mV		
Ripple & Noise (5Hz-1MHz)	≤2mVrms		
Transient Recovery Time	≤100μs (50% load change , minimum load)		
Temperature Coefficient	≤ 300ppm/°C		
CONSTANT CURRENT OPERATION			
Line Regulation	≤ 0.01% + 3mA		
Load Regulation	≤ 0.01% + 3mA		
Ripple & Noise	≤ 2mA rms		
RESOLUTION			
Programming	Voltage/Current	1mV / 0.2mA	2mV / 0.1mA
Reedback	Voltage/Current	0.1mV / 0.2mA	0.1mV / 0.1mA
METER			
Full Scale	Voltage/Current	36.5000V / 10.2000A	72.5000V / 5.2000A
Programming Resolution	Voltage/Current	5 digits / 6 digits	
Reedback Resolution	Voltage/Current	6 digits / 6 digits	
Setting Accuracy	Voltage	± (0.03% of reading + 10mV)	
	Current	± (0.3% of reading + 10mA)	
Readback Accuracy	Voltage	± (0.03% of reading + 10mV)	
	Current	± (0.3% of reading + 10mA)	
DC LOAD MODE			
Display	Voltage	1 ~ 36.50V	1 ~ 72.50V
	Current	0 ~ 10.200A	0 ~ 5.200A
	Power	0 ~ 100.00W	0 ~ 100.00W
CV Mode	CH1	1.500V ~ 36.50V	1.500V ~ 72.50V
	Setting/Reedback Accuracy	≤±(0.1% + 30mV)	≤±(0.1% + 30mV)
	Resoltion	10mV	10mV
CC Mode	CH1	0 ~ 10.200A	0 ~ 5.200A
	Setting/Reedback Accuracy	≤±(0.3% + 10mA)	≤±(0.3% + 10mA)
	Resoltion	1mA	1mA
CR Mode	CH1	1Ω ~ 1kΩ	1Ω ~ 1kΩ
	Setting/Reedback Accuracy	≤±(3% + 1Ω) (voltage≥0.1V, and current≥0.1A)	≤±(3% + 1Ω) (voltage≥0.1V, and current≥0.1A)
	Resoltion	1Ω	1Ω
PROTECTION			
OVP	Power Mode	OFF,ON(0.5V ~ 38.0V)	OFF,ON(0.5V ~ 75.0V)
	Load Mode	OFF,ON(1.5V ~ 38.0V)	OFF,ON(1.5V ~ 75.0V)
	Setting Accuracy	±100mV	
	Resoltion	100mV	
OCP	Power Mode	OFF,ON(0.05A ~ 10.5A)	OFF,ON(0.05A ~ 5.50A)
	Load Mode	OFF,ON(0.05A ~ 10.5A)	OFF,ON(0.05A ~ 5.50A)
	Setting Accuracy	±20mA	
	Resoltion	10mA	
Insulation Resistance		Between chassis and terminal : 20MΩ or above (DC 500V) Between chassis and DC power cord : 30MΩ or above (DC 500V)	
GENERAL			
Operation Environment		Indoor use, Altitude: ≤ 2000m Ambient temperature: 0 ~ 40°C / Relative humidity: ≤ 80% Installation category: II / Pollution degree: 2	
Storage Environment		TEMPERATURE: -10°C ~ 70°C / HUMIDITY: ≤70%	
Power Input		AC 100V/120V/220V/230V±10%, 50/60Hz	
Power Consumption		900VA, 680W	
Dimensions & Weight		213 (W) x 145 (H) x 362 (D) mm ; Approx. 10kg	