



# 34000A 系列

超高功率直流電子負載

## 特點

- 最大功率可達 320 KW
- 最高達 8 台主/從並聯控制
- 5位數之數位電壓、電流以及功率錶
- 可自動執行OCP、OPP測試
- 可設定開機狀態值
- 於短路測試時可設定短路時間
- 電壓極性顯示可設成正值（" + "）或負值（" - "）
- 支援太陽能板MPPT CC、CR、CV測試
- 內建緩啟動電路功能，允許UUT電源直接連接到342XA、343XA系列負載輸入端，不再需要外接緩啟動電路的大型繼電器開關

# 34000A 系列 超高功率直流電子負載



## 特 性

- 最大功率可達 320 KW
- 最高達 8 台主/從並聯控制
- 5位數之數位電壓、電流以及功率錶
- 高速量測及通訊傳輸速率
- 大型 LCD Display、可用飛梭旋鈕或按鍵調整設定值
- 可同時顯示電壓值、電流值、瓦特值
- 適用於功率因數調整器(PFC)測試用 (600 V,1000 V機種)
- 可自動執行OCP、OPP測試
- 定電流、定電阻、定電壓、定功率、定電流+定電壓、定功率+定電壓、動態及短路模式
- 可設定開機狀態值
- 於短路測試時可設定短路時間
- 過電流、功率、溫度保護及過電壓示警
- 電壓極性顯示可設成正值 (“+”) 或負值 (“-”)
- 支援太陽能板MPPT CC、CR、CV測試
- 可選用介面：GPIB、RS232、USB、LAN
- 內建緩啟動電路功能，允許UUT電源直接連接到342XA、343XA系列負載輸入端，不再需要外接緩啟動電路的大型繼電器開關

## 說 明

- 34000A系列具有獨立的控制及顯示面板、定電流/定電阻/定電壓/定功率/動態模式，配合面板上的150組 儲存/呼叫 記憶，能有效地控制所有負載的設定，更可透過RS232、Ethernet、USB和GPIB等介面進行遠端控制。
- 具備短路測試功能及設定短路時間，並可量測短路電壓及電流。
- 在定電流及定功率模式下，可做動態負載之模擬，其電流上升、下降斜率均為獨立可調，另具有-外部輸入任意波形之動態負載功能。
- 具有OCP、OPP單鍵測試功能，使得OCP、OPP之測試更有效率及準確。
- 可設定的吃載/停止吃載(LOAD ON/OFF)電壓點及良/不良(GO/NG)的比較判斷功能、電壓極性顯示可正可負及150組 儲存/呼叫 記憶，使得負載更適用於各種不同的應用。
- 多達150組測試參數及狀態的儲存功能，讓其可根據自動測試 (auto sequence) 需求，隨時將儲存記憶調出來任意使用。
- 因其耐壓可高達1000 V，故而非常適用於功率因數調整器 (PFC) 的測試應用。
- 主/從控制最多為1個MASTER，7個SLAVE

## 應 用

- 電壓/電流源測試
- 交換式電源供應器暫態響應
- 定電壓模式供限流測試及模擬電池
- 電池放電
- 電池充電
- 研發、品管
- ATE系統
- 生產測試

## SPECIFICATIONS

Model	34130A		34135A		34140A	
Power	30 kW	30 kW	35 kW	35 kW	40 kW	40 kW
Current	0 A to 100 A	0 A to 1000 A	0 A to 100 A	0 A to 1000 A	0 A to 100 A	0 A to 1000 A
Voltage	0 V to 60 V					
Min. Operating Voltage	0.1 V @ 100 A	0.7 V @ 1000 A *1	0.1 V @ 100 A	0.7 V @ 1000 A *1	0.1 V @ 100 A	0.7 V @ 1000 A *1
<b>Protections</b>						
Over Power Protection(OPP)	105 %					
Over Current Protection(OCP)	104 %					
Over Voltage Protection(OVP)	105 %					
Over Temp Protection(OTP)	YES					
<b>Constant Current Mode</b>						
Range *2	100 A	1000 A	100 A	1000 A	100 A	1000 A
Resolution	1.6 mA	16 mA	1.6 mA	16 mA	1.6 mA	16 mA
Accuracy	± 0.05 % of (Setting + Range)					
<b>Constant Resistance Mode</b>						
Range	3600 Ω to 0.06 Ω	0.06 Ω to 0.001 Ω	3600 Ω to 0.06 Ω	0.06 Ω to 0.001 Ω	3600 Ω to 0.06 Ω	0.06 Ω to 0.001 Ω
Resolution	277 μS *5	0.001 mΩ	277 μS *5	0.001 mΩ	277 μS *5	0.001 mΩ
Accuracy	± 0.2 % of (Setting + Range)					
<b>Constant Voltage Mode</b>						
Range	60 V					
Resolution	1 mV					
Accuracy	± 0.05 % of (Setting + Range)					
<b>Constant Power Mode</b>						
Range	3000 W	30000 W	3500 W	35000 W	4000 W	40000 W
Resolution	48 mW	480 mW	56 mW	560 mW	64 mW	640 mW
Accuracy	± 0.1 % of (Setting + Range)					
<b>Constant Voltage + Current Limit Mode</b>						
Range	60 V	1000 A	60 V	1000 A	60 V	1000 A
Resolution	1 mV	16 mA	1 mV	16 mA	1 mV	16 mA
Accuracy	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)
<b>Constant Voltage + Power Limit Mode</b>						
Range	60 V	30000 W	60 V	35000 W	60 V	40000 W
Resolution	1 mV	480 mW	1 mV	560 mW	1 mV	640 mW
Accuracy	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)
<b>MPPT Mode</b>						
Algorithm	P & O					
Load mode	CV					
P&O interval	1000 ms to 60000 ms ; resolution 1000 ms					
<b>Dynamic Mode</b>						
<b>Timing</b>						
Thigh & Tlow	0.150 ms to 9.999 ms / 99.99 ms / 999.9 ms / 9999 ms					
Resolution	0.001 ms / 0.01 ms / 0.1 ms / 1 ms					
Accuracy	1 μS / 10 μS / 100 μS / 1 mS + 50 ppm					
Slew rate	24 mA/μs to 1.5 A/μs	240 mA/μs to 15 A/μs	24 mA/μs to 1.5 A/μs	240 mA/μs to 15 A/μs	24 mA/μs to 1.5 A/μs	240 mA/μs to 15 A/μs
Resolution	6 mA/μs	60 mA/μs	6 mA/μs	60 mA/μs	6 mA/μs	60 mA/μs
Min. Rise Time	66.7 μs (typical)					
Accuracy	± (5 % of Setting) ± 10 μs					
<b>Current</b>						
Range	0 A to 100 A	100 A to 1000 A	0 A to 100 A	100 A to 1000 A	0 A to 100 A	100 A to 1000 A
Resolution	1.6 mA	16 mA	1.6 mA	16 mA	1.6 mA	16 mA
<b>Measurement</b>						
<b>Voltage Read Back</b>						
Range (5 Digital)	0 V to 6 V	6 V to 60 V	0 V to 6 V	6 V to 60 V	0 V to 6 V	6 V to 60 V
Resolution	0.1 mV	1 mV	0.1 mV	1 mV	0.1 mV	1 mV
Accuracy	± 0.025 % of (Reading + Range)					
<b>Current Read Back</b>						
Range (5 Digital)	0 A to 100 A	100 A to 1000 A	0 A to 100 A	100 A to 1000 A	0 A to 100 A	100 A to 1000 A
Resolution	1.6 mA	16 mA	1.6 mA	16 mA	1.6 mA	16 mA
Accuracy	± 0.05 % of (Reading + Range)					
<b>Power Read Back</b>						
Range (5 Digital)	3000 W	30000 W	3500 W	35000 W	4000 W	40000 W
Resolution	0.1 W	1 W	0.1 W	1 W	0.1 W	1 W
Accuracy *3	± 0.06 % of (Reading + Range)					
<b>General</b>						
<b>Short Circuit</b>						
Current	1000 A					
Load ON Voltage	0.1 V to 25 V					
Load OFF Voltage	0 V to 25 V					
Power Consumption	2800 Wmax		3250 Wmax		3700 Wmax	
Dimension(HxWxD)	1197 mm x 647 mm x 766 mm		1353 mm x 647 mm x 766 mm		1509 mm x 647 mm x 766 mm	
Weight	340 Kg		390 Kg		430 Kg	
<b>Operating Range</b>						
Temperature *4	0 °C to 40 °C					
Humidity	20 % to 85 %rh					
<b>Storage Range</b>						
Temperature	-20 °C to +70 °C					
Humidity	≤ 90 %rh					
<b>Withstanding Voltage test</b>						
AC input and FG	AC 1500 V, 1 minute.					
AC input and Load terminal	AC 3000 V, 1 minute.					
Load terminal and FG	AC 1500 V, 1 minute.					
Safety & EMC	CE					

Note \*1 : 0.7 V @ 1000 A is on Static condition, and the starting voltage must be greater than 5 V, if on Dynamic condition that is 5 V @ 1000 A

Note \*2 : The range is automatically or forcing to range II only in CC mode

Note \*3 : Power F.S. = Vrange F.S. x Irange F.S.

Note \*4 : Operating temperature range is 0 °C to 40 °C, All specifications apply for 25 °C±5 °C, Except as noted

Note \*5 : μS

(microsiemens) is the unit

of conductance(G), one

Input AC Power : 100 Vac to 230 Vac ± 10 %, 50/60 Hz

Cooling : Advanced Fan Cooled

All specifications are subject to change without notice.



## SPECIFICATIONS

Model	34230A		34235A		34240A	
Power	30 KW	30 KW	35 KW	35 KW	40 KW	40 KW
Current	0 A to 96 A	0 A to 960 A	0 A to 112 A	0 A to 1120 A	0 A to 128 A	0 A to 1280 A
Voltage	0 V to 600 V					
Min. Operating Voltage	20V @ 960A		20V @ 1120A		20V @ 1280A	
<b>Protections</b>						
Over Power Protection(OPP)	105 %					
Over Current Protection(OCP)	104 %					
Over Voltage Protection(OVP)	105 %					
Over Temp Protection(OTP)	YES					
<b>Constant Current Mode</b>						
Range *1	96 A	960 A	112 A	1120 A	128 A	1280 A
Resolution	1.536 mA	15.36 mA	1.792 mA	17.92 mA	2.048 mA	20.48 mA
Accuracy	± 0.05 % of (Setting + Range)					
<b>Constant Resistance Mode</b>						
Range	12500 Ω to 0.625 Ω	0.625 Ω to 0.0105 Ω	32142 Ω to 0.5357 Ω	0.5357 Ω to 0.009 Ω	28125 Ω to 0.46875 Ω	0.46875 Ω to 0.0078 Ω
Resolution *4	26.6 μS	0.0105 mΩ	31.1 μS	0.009 mΩ	35.5 μS	0.007875 mΩ
Accuracy	± 0.2 % of (Setting + Range)					
<b>Constant Voltage Mode</b>						
Range	600 V		600 V		600 V	
Resolution	10 mV		10 mV		10 mV	
Accuracy	± 0.05 % of (Setting + Range)					
<b>Constant Power Mode</b>						
Range	3000 W	30000 W	3500 W	35000 W	4000 W	40000 W
Resolution	48 mW	480 mW	56 mW	560 mW	64 mW	640 mW
Accuracy	± 0.1 % of (Setting + Range)					
<b>Constant Voltage + Current Limit Mode</b>						
Range	600 V	960 A	600 V	1120 A	600 V	1280 A
Resolution	10 mV	15.36 mA	10 mV	17.92 mA	10 mV	20.48 mA
Accuracy	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)
<b>Constant Voltage + Power Limit Mode</b>						
Range	600 V	30000W	600 V	35000W	600 V	40000W
Resolution	10 mV	480mW	10 mV	560mW	10 mV	640mW
Accuracy	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)
<b>MPPT Mode</b>						
Algorithm	P&O					
Load mode	CV					
P&O interval	1000 ms to 60000 ms ; resolution 1000 ms					
<b>Dynamic Mode</b>						
<b>Timing</b>						
Thigh & Tlow	0.050 ms to 9.999 ms / 99.99 ms / 999.9 ms / 9999 ms					
Resolution	0.001 ms / 0.01 ms / 0.1 ms / 1 ms					
Accuracy	1 μS/10 μS/100 μS/1 ms + 50 ppm					
Slew rate	76.8 mA/μs to 4.8 A/μs	768 mA/μs to 48 A/μs	89.6 mA/μs to 5.6 A/μs	896 mA/μs to 56 A/μs	102.4 mA/μs to 6.4 A/μs	1024 mA/μs to 64 A/μs
Resolution	19.2 mA/μs	192 mA/μs	22.4 mA/μs	224 mA/μs	25.6 mA/μs	256 mA/μs
Min. Rise Time	20 μs(typical)					
Accuracy	± (5 % of Setting) ±10 μs					
Current						
Range	0 A to 96 A	96 A to 960 A	0 A to 112 A	112 A to 1120 A	0 A to 128 A	128 A to 1280 A
Resolution	1.536 mA	15.36 mA	1.792 mA	17.92 mA	2.048 mA	20.48 mA
<b>Measurement</b>						
<b>Voltage Read Back</b>						
Range (5 Digital)	0 V to 60 V	60 A to 600 V	0 V to 60 V	60 A to 600 V	0 V to 60 V	60 A to 600 V
Resolution	1 mV	10 mV	1 mV	10 mV	1 mV	10 mV
Accuracy	± 0.025 % of (Reading + Range)					
<b>Current Read Back</b>						
Range (5 Digital)	0 A to 96 A	96 A to 960 A	0 A to 112 A	112 A to 1120 A	0 A to 128 A	128 A to 1280 A
Resolution	1.536 mA	15.36 mA	1.792 mA	17.92 mA	2.048 mA	20.48 mA
Accuracy	± 0.05 % of (Reading + Range)					
<b>Power Read Back</b>						
Range (5 Digital)	3000 W	30000 W	3500 W	35000 W	4000 W	40000 W
Resolution	0.1 W	1 W	0.1 W	1 W	0.1 W	1 W
Accuracy *2	± 0.06 % of (Reading + Range)					
<b>General</b>						
<b>Short Circuit</b>						
Current	960 A		1120 A		1280 A	
Load ON Voltage	0.4 V to 100 V					
Load OFF Voltage	0 V to 100 V					
Power Consumption	2800 Wmax		3250 Wmax		3700 Wmax	
Dimension(HxWxD)	1197 mm x 647 mm x 766 mm		1353 mm x 647 mm x 766 mm		1509 mm x 647 mm x 766 mm	
Weight	340 Kg		390 Kg		430 Kg	
<b>Operating Range</b>						
Temperature *3	0 °C to 40 °C					
Humidity	20 % to 85 %rh					
<b>Storage Range</b>						
Temperature	-20 °C to +70 °C					
Humidity	≤ 90 %rh					
<b>Withstanding Voltage test</b>						
AC input and FG	AC 1500 V, 1 minute.					
AC input and Load terminal	AC 3000 V, 1 minute.					
Load terminal and FG	AC 1500 V, 1 minute.					
Safety & EMC	CE					

Note \*1 : The range is automatically or forcing to range II only in CC mode

Note \*2 : Power F.S. = Vrange F.S. x Irange F.S.

Note \*3 : Operating temperature range is 0 °C to 40 °C, All specifications apply for 25 °C±5 °C, Except as noted

Note \*4 : μS (microsiemens) is the unit of conductance(G), one siemens equal to 1/

Input AC Power : 100 Vac to 230 Vac ± 10 %, 50/60 Hz

Cooling : Advanced Fan Cooled

All specifications are subject to change without notice.



## SPECIFICATIONS

Model	34330A		34335A		34340A	
Power	30 KW	30 KW	35 KW	35 KW	40 KW	40 KW
Current	0 A to 30 A	0 A to 300 A	0 A to 35 A	0 A to 350 A	0 A to 40 A	0 A to 400 A
Voltage			0 V to 1000 V			
Min. Operating Voltage	30 V @ 300 A		30 V @ 350 A		30 V @ 400 A	
<b>Protections</b>						
Over Power Protection(OPP)			105 %			
Over Current Protection(OCP)			104 %			
Over Voltage Protection(OVP)			104 %			
Over Temp Protection(OTP)			YES			
<b>Constant Current Mode</b>						
Range *1	30 A	300 A	35 A	350 A	40 A	400 A
Resolution	0.48 mA	4.8 mA	0.56 mA	5.6 mA	0.64 mA	6.4 mA
Accuracy						
<b>Constant Resistance Mode</b>						
Range	4000 Ω to 3.333 Ω	3.333 Ω to 0.033396 Ω	3428.4 Ω to 2.857 Ω	2.857 Ω to 0.02862 Ω	3000 Ω to 2.5 Ω	2.5 Ω to 0.02505 Ω
Resolution *4	5 μs	0.05566 mΩ	5.83 μs	0.047711 mΩ	6.66 μs	0.04175 mΩ
Accuracy	± 0.2 % of (Setting + Range)					
<b>Constant Voltage Mode</b>						
Range	10 V to 1000 V					
Resolution	16 mV					
Accuracy	± 0.05 % of (Setting + Range)					
<b>Constant Power Mode</b>						
Range	3000 W	30000 W	3500 W	35000 W	4000 W	40000 W
Resolution	48 mW	480 mW	56 mW	560 mW	64 mW	640 mW
Accuracy	± 0.1 % of (Setting + Range)					
<b>Constant Voltage + Current Limit Mode</b>						
Range	1000 V	300 A	1000 V	350 A	1000 V	400 A
Resolution	16 mV	4.8 mA	16 mV	5.6 mA	16 mV	6.4 mA
Accuracy	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)
<b>Constant Voltage + Power Limit Mode</b>						
Range	1000 V	30000 W	1000 V	35000 W	1000 V	40000 W
Resolution	16 mV	480 mW	16 mV	560 mW	16 mV	640 mW
Accuracy	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)	± 0.05 % of (Setting + Range)	± 1.0 % of (Setting + Range)
<b>MPPT Mode</b>						
Algorithm	P&O					
Load mode	CV					
P&O interval	1000 ms to 60000 ms ; resolution 1000 ms					
<b>Dynamic Mode</b>						
<b>Timing</b>						
Thigh & Tlow	0.050 ms to 9.999 ms / 99.99 ms / 999.9 ms / 9999 ms					
Resolution	0.001 ms / 0.01 ms / 0.1 ms / 1 ms					
Accuracy	1 μs / 10 μs / 100 μs / 1 ms + 50 ppm					
Slew rate	0.024 A/μs to 1.5 A/μs	0.24 A/μs to 15 A/μs	0.028 A/μs to 1.75 A/μs	0.28 A/μs to 17.5 A/μs	0.032 A/μs to 2 A/μs	0.32 A/μs to 20 A/μs
Resolution	0.006 A/μs	0.06 A/μs	0.007 A/μs	0.07 A/μs	0.008 A/μs	0.08 A/μs
Min. Rise Time	20 μs (typical)					
Accuracy	± (5 % of Setting) ± 10 μs					
<b>Current</b>						
Range	0 A to 30 A	30 A to 300 A	0 A to 35 A	35 A to 350 A	0 A to 40 A	40 A to 400 A
Resolution	0.48 mA	4.8 mA	0.56 mA	5.6 mA	0.64 mA	6.4 mA
<b>Measurement</b>						
<b>Voltage Read Back</b>						
Range (5 Digital)	0 V to 100 V	100 V to 1000 V	0 V to 100 V	100 V to 1000 V	0 V to 100 V	100 V to 1000 V
Resolution	1.6 mV	16 mV	1.6 mV	16 mV	1.6 mV	16 mV
Accuracy	± 0.025 % of (Reading + Range)					
<b>Current Read Back</b>						
Range (5 Digital)	0 A to 30 A	30 A to 300 A	0 A to 35 A	35 A to 350 A	0 A to 40 A	40 A to 400 A
Resolution	0.48 mA	4.8 mA	0.56 mA	5.6 mA	0.64 mA	6.4 mA
Accuracy	± 0.05 % of (Reading + Range)					
<b>Power Read Back</b>						
Range (5 Digital)	3000 W	30000 W	3500 W	35000 W	4000 W	40000 W
Resolution	0.1 W	1 W	0.1 W	1 W	0.1 W	1 W
Accuracy *2	± 0.06 % of (Reading + Range)					
<b>General</b>						
<b>Short Circuit</b>						
Current	300 A		350 A		400 A	
Load ON Voltage	10.4 V to 200 V					
Load OFF Voltage	0 V to 200 V					
Power Consumption	2800 Wmax		3250 Wmax		3700 Wmax	
Dimension(HxWxD)	1197 mm x 647 mm x 766 mm		1353 mm x 647 mm x 766 mm		1509 mm x 647 mm x 766 mm	
Weight	340 Kg		390 Kg		430 Kg	
<b>Operating Range</b>						
Temperature *3	0 °C to 40 °C					
Humidity	20 % to 85 %rh					
<b>Storage Range</b>						
Temperature	-20 °C to +70 °C					
Humidity	≤ 90 %rh					
<b>Withstanding Voltage test</b>						
AC input and FG	AC 1500 V, 1 minute.					
AC input and Load terminal	AC 3000 V, 1 minute.					
Load terminal and FG	AC 1500 V, 1 minute.					
Safety & EMC	CE					

Note \*1 : The range is automatically or forcing to range II only in CC mode

Note \*2 : Power F.S. = Vrange F.S. x Irange F.S.

Note \*3 : Operating temperature range is 0 °C to 40 °C, All specifications apply for 25 °C±5 °C, Except as noted

Note \*4 : μS (microsiemens) is the unit of conductance(G), one siemens equal to 1/

Input AC Power : 100 Vac to 230 Vac ± 10 %, 50/60 Hz

Cooling : Advanced Fan Cooled

All specifications are subject to change without notice.



## 購買資訊

<b>34130A</b>	超高功率直流電子負載	60 V / 1000 A / 30 kW
<b>34135A</b>	超高功率直流電子負載	60 V / 1000 A / 35 kW
<b>34140A</b>	超高功率直流電子負載	60 V / 1000 A / 40 kW
<b>34230A</b>	超高功率直流電子負載	600 V / 960 A / 30 kW
<b>34235A</b>	超高功率直流電子負載	600 V / 1120 A / 35 kW
<b>34240A</b>	超高功率直流電子負載	600 V / 1280 A / 40 kW
<b>34330A</b>	超高功率直流電子負載	1000 V / 300 A / 30 kW
<b>34335A</b>	超高功率直流電子負載	1000 V / 350 A / 35 kW
<b>34340A</b>	超高功率直流電子負載	1000 V / 400 A / 40 kW



RS232 介面



GPIOB 介面



USB 介面



LAN 介面



### STANDARD ACCESSORIES

Banana Plug x 2 PCs  
 BNC-BNC CABLE L=1M x 1 PC  
 HD-DSUB 15PIN Parallel Cable x 1 PC  
 Hex Head Screw M8\*1.25 L=35mm NI x4 PCs

Round Head Phillips Screw M8\*1.25 L=35mm NI x4 PCs  
 NUT M8 x 1.25 NI x 4 PCs  
 WASHER INSIDE DIA-8.5 OUTSIDE x 8 PCs  
 Power Cord x 1 PC

### OPTIONAL ACCESSORIES

RS232 介面 Hook Ring  
 GPIOB 介面 GPIOB 纜線長度 1 米  
 USB 介面 GPIOB 纜線長度 2 米  
 LAN 介面 USB TYPE A to TYPE B 連接電纜線長度 1.8 米

GTL-170 1000安培銅編織帶 (單孔) 1M ,2條  
 GTL-171 1000安培銅編織帶 (單孔) 2M ,2條  
 GTL-172 1000安培銅編織帶 (單孔) 3M ,2條  
 GTL-173 1000安培銅編織帶 (單孔) 4M ,2條  
 GTL-174 1000安培銅編織帶 (單孔) 5M ,2條  
 GTL-175 500安培銅編織帶 (單孔) 1M ,2條  
 GTL-176 500安培銅編織帶 (單孔) 2M ,2條  
 GTL-177 500安培銅編織帶 (單孔) 3M ,2條  
 GTL-178 500安培銅編織帶 (單孔) 4M ,2條

Note: \* Regarding the product delivery date, please contact your regional sales representative.

規格若有局部變更，恕不另行通知！ 34000A\_BH1\_C\_202507

#### 固緯電子實業股份有限公司

新北市土城區中興路 7-1 號  
T (02)2268-0389 F (02)2268-0639  
E-mail: marketing@goodwill.com.tw

高雄 高雄市前鎮區新街路286之4號7樓之1  
T (07) 831-7317 F (07) 831-7327

#### 固緯電子(蘇州)有限公司

江蘇省蘇州市新區珠江路521號  
T 0512-6661-7177 F 0512-6661-7277  
E-mail: marketing@instek.com.cn

上海 上海市宜山路 889 號 2 號樓 8 樓  
T 021-6485-3399 F 021-5450-0789

深圳 深圳市寶安區航城街道三圍社區泰華梧桐工業園138棟6樓  
T 0755-2919-0632 F 0755-2907-6570

**GW INSTEK**  
Simply Reliable



 產品操作影片



 最新活動訊息



 產品資料價格進型技術諮詢